# ≅MAVERICK™ X3 MAX X™ ds TURBO R

#### HIGHLIGHTS

#### DEFIANT

- Trademark Can-Am DNA with next generation design
- Low seating position
- Ergo-Lok cockpit with front and rear four-way adjustable seats

### **POWERFUL**

- Industry leading 172 hp turbocharged and intercooled Rotax® ACE engine
- Advanced airflow dynamics
- QRS-X transmission

#### PRECISE

- TTX suspension with industry leading travel
- Ultra efficient and lightweight chassis
- Sharpest handling features



Platinum Satin / TURBO R
Phoenix Orange / TURBO R

Triple Black / TURBO R

## SPECIFIC TO X ds PACKAGE

- 64-in. (162.5 cm) wide
- Smart-Lok<sup>TM\*</sup> Full lockable on-the-fly front differential with electronically-controlled automatic modes
- 14-in. aluminum beadlock wheels with 29-in. Maxxis Bighorn<sup>†</sup> 2.0 tires
- Front and rear 20-in. suspension travel
- Fully adjustable FOX<sup>†</sup> 2.5 PODIUM RC2<sup>†</sup> Piggyback shocks
- Painted color options

ENGINE	TURBO R
Туре	172 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and Donaldson† high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok * technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL
	*Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)


<b>SUSPENSIONS</b>		
Front Suspension	Double A-arm with sway bar 20 in. (50.8 cm) travel	
Front Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression and rebound adjustments	
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar 20 in. (50.8 cm) travel	
Rear Shocks	FOX 2.5 PODIUM RC2 Piggyback with dual speed compression, rebound adjustments and bottom-out control	
BRAKES		
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers	
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers	

TIRES / WHEEL	<b>.</b> \$
Front Tires	Maxxis Bighorn 2.0 29 x 9 x 14 in. (73.7 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 29 x 11 x 14 in. (73.7 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) cast-aluminum beadlock

DIMENSIONS / CAPACITIES		
LxWxH	164 x 64 x 66 in. (416.6 x 162.5 x 167.6 cm)	
Wheelbase	135 in. (342.9 cm)	
Ground Clearance	13 in. (33 cm)	
Estimated Dry Weight	1,735 lb (786.9 kg)	
Cage / Chassis	Dual-phase 980 steel, fully welded	
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach	
Storage Capacity	Total: 3 gal (11.4 L) Glove box: 1.6 gal (6.2 L) Center console: 1.1 gal (4.1 L) Cup holders: 0.3 gal (1.1 L)	
Fuel Capacity	10.5 gal (40 L)	

<b>FEATURES</b>			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour	Protection	Integrated front bumper, full High Molecular Weight (HMW) skid plate and quarter-doors
	meters, fuel, gear position, sport / ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock,	Instrumentation	Lighter type DC outlet in central console
	auto shut off	Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	N/A	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage







Can-AmOffroad.com