



# DIESEL Z



AVAILABLE DECK SIZES

Engine	Deck Sizes
25HP* - Perkins	60", 72" • 60" RD, 72" RD


LIMITED WARRANTY

**5** YEAR | **1200** HOUR

FIRST 2 YEARS NO HOUR LIMIT



**VX4® Deck**  
Fabricated 7 ga. steel deck engineered to move large amounts of grass at high speeds while maintaining cut-quality.



**13M™ Suspension Seat**  
High-back seat with adjustable armrests and 3-inch travel range.



**Patented Belt Drive System**  
Helps provide long-life to the machine.

DIESEL Z				
Deck	60"	60" RD	72"	72" RD
MSRP	\$25,999	\$26,699	\$26,399	\$26,999
Contractor Pricing	\$20,799	\$21,359	\$21,119	\$21,599
<b>ENGINE</b>				
Manufacturer	Perkins			
HP	25HP* (Per SAE J1995)			
Displacement	1,130cc			
Cooling	Liquid cooled, direct-drive, mechanical cooling fan			
Air Cleaner	Remote canister			
Engine Warranty	3 year limited			
<b>DRIVE SYSTEM</b>				
Type	Dual hydrostatic			
Pumps	Tandem 21cc Hydro-Gear® pumps			
Wheel Motors	Parker® TG			
Hydraulic Lines	Stainless steel Parker® Seal-Lok technology			
Hydraulic Cooling	Oil cooler with 8" fan			
Reservoir Capacity	1.3 gallons			
Speed	Up to 11.5 mph			
Parking Brakes	Integrated with steering levers			
<b>DECKS</b>				
Cutting Width	Side discharge: 60", 72" • Rear-discharge: 60", 72"			
Cutting Heights	1" - 5.5"			
Deck Lift	Foot operated			
Depth	5.5"			
Blades	3			
Blade Length	60" deck: 20.50" • 72" deck: 24.5"			
Blade Tip Speed	60": 18,200 • 72": 18,800			
Spindles	Ductile cast iron with steel shaft and sealed ball bearings			
Drive	Electric PTO clutch			
Construction	7 ga. welded steel			
Spindle Mounts	Reinforced 7 ga. stamped disc			
Impact/Trim Areas	Front of deck: 11 ga. formed bump bar • Side of deck: 1.5" x .375" steel bar			
<b>CONSTRUCTION</b>				
Frame	1.5" x 3" steel tubing			
Front Axle	Fabricated w/ sealed ball bearings			
Front Caster Wheels	Tapered wheel bearings and debris cap			
Front Caster Forks	Fabricated 1/2" steel			
<b>GENERAL</b>				
Seat	I3M™ suspension seat			
Fuel Capacity	14.4 gallons			
Cupholder	Yes			
Front Tire	13 x 6.5 - 6			
Drive Tire	24 x 12 - 12			
<b>DIMENSIONS</b>				
Weight	60": 1656 lbs • 60"RD: 1766 lbs • 72": 1711 lbs • 72"RD: 1816 lbs			
Height	51" • 69" w/ ROPs			
Length	60", 60"RD: 86.8" • 72", 72"RD: 90.4"			
Width w/Chute Up	60", 60"RD: 66" • 72", 72"RD: 78"			
Tire Width	56"			
Trim Side	60": 3.9" • 60"RD: 3.6" • 72": 10.9" • 72"RD: 8.6"			
<b>PRODUCTIVITY**</b>				
Acres Per Hour	60": 5.57 • 72": 6.68			

Specifications are subject to change without notice.

## ACCESSORIES

(Each sold separately)

- ▶ Semi pneumatic front tires
- ▶ Steering lever extension kit
- ▶ Single/dual anti-scalp wheels
- ▶ Flex Forks®
- ▶ Mulch kit
- ▶ Light kit
- ▶ Stripe kit
- ▶ Sand kit
- ▶ Beacon kit
- ▶ Flasher kit
- ▶ Electric deck lift
- ▶ Hitch kit
- ▶ Michelin® X® Tweel® Turf
- ▶ Michelin® X® Tweel® Turf Caster
- ▶ Fabric side catcher (3.5 bu)
- ▶ Aluminum side catcher (3.3 bu)

\* As rated by the engine manufacturer.  
 \*\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.  
 Parker is a registered trademark owned by Parker Intangibles LLC. Hydro-Gear is a registered trademark owned by Hydro-Gear Limited Partnership.  
 Michelin, X and Tweel are registered trademarks owned by COMPAGNIE GÉNÉRALE DES ÉTABLISSEMENTS MICHELIN.