



TRIMSTAR



AVAILABLE DECK SIZES

Engine	Deck Sizes
15HP* - Kawasaki® FS541 (Electric Start)	36"
18.5HP* - Kawasaki® FS600 (Electric Start)	48"
22HP* - Kawasaki® FS651 (Electric Start)	54"
23HP* - Kawasaki® FS691 (Electric Start)	60"



H-bar® Steering
Patented, easy-to-use steering helps with training new operators and minimize operator fatigue.



Comfort-designed controls
Helps minimize operator fatigue.



Compact stance
Excellent maneuvering in tight spaces.

TRIMSTAR

Deck	36"	48"	54"	60"
MSRP	\$9,699	\$9,999	\$10,899	\$11,399
Contractor Pricing	\$7,759	7,999	\$8,719	\$9,119
ENGINE				
Manufacturer	Kawasaki®			
HP	36" deck: 15HP* - FS541 (Electric Start) 48" deck: 18.5HP* - FS600 (Electric Start) 54" deck: 22HP* - FS651 (Electric Start) 60" deck: 23HP* - FS691 (Electric Start) (Per SAE J1995)			
Displacement	FS541, FS600: 603cc • FS651, FS691: 726cc			
Cooling	Air cooled			
Air Cleaner	Oval Canister, dual element			
Engine Warranty	3 year limited			
DRIVE SYSTEM				
Type	Dual hydrostatic			
Transmission	Hydro-Gear® ZT-2800®			
Hydraulic Cooling	Pump mounted fans			
Speed	Up to 6.3 mph			
Parking Brakes	Internal transmission mechanical brake			
DECKS				
Cutting Width	Side discharge: 36", 48", 54", 60"			
Cutting Heights	1.5"- 4.5"			
Deck Lift	Hand operated			
Depth	5"			
Blades	36" deck: 2 • 48", 54", 60" decks: 3			
Blade Length	36" deck: 17.86" • 48" deck: 16.50" 54" deck: 18.50" • 60" deck: 20.50"			
Blade Tip Speed	36" deck: 18,400 • 48" deck: 18,500 • 54" deck: 18,800 • 60" deck: 18,400			
Spindles	Aluminum with steel shaft and sealed ball bearings			
Drive	Electric PTO clutch			
Construction	36" deck: 7 ga. + 11 ga. reinforced steel • 48", 54", 60" deck: 10ga. + 11ga. reinforced steel			
Impact/Trim Areas	11ga. formed channel rolled edge			
CONSTRUCTION				
Frame	1.5" x 2.0" steel tubing			
Front Axle	Fabricated with tapered roller bearings			
Front Caster Wheels	Tapered wheel bearings and debris cap			
Front Caster Forks	Fabricated 3/8" steel			
GENERAL				
Fuel Capacity	3.4 gallons			
Cupholder	No			
Front Tire	11 x 4 - 5 semi pneumatic			
Drive Tire	36" deck: 20 x 6.5 - 10 • 48" deck: 20 x 8 - 10 • 54", 60" deck: 20 x 10 - 10			
DIMENSIONS				
Weight	36" deck: 560 lbs • 54" deck: 660 lbs 48" deck: 635 lbs • 60" deck: 695 lbs			
Height	42.5"			
Length	36" deck: 76.7" • 48" deck: 75" • 54" deck: 75.3" • 60" deck: 77.5"			
Width w/Chute Up	36" deck: 37" • 48" deck: 49" • 54" deck: 55" • 60" deck: 61"			
Tire Width	36" deck: 35" • 48" deck: 44" • 54" deck: 46" • 60" deck: 46"			
Trim Side	36" deck: 0.9" • 48" deck: 2.4" • 54" deck: 5.5" • 60" deck: 8.4"			
PRODUCTIVITY**				
Acres Per Hour	36" deck: 1.88 • 48" deck: 2.44 • 54" deck: 2.75 • 60" deck: 3.06			

Specifications are subject to change without notice.

ACCESSORIES

(Each sold separately)

- ▶ Mesh side bagger (3 bushels)
- ▶ Steel side bagger (4.4 cu. ft.)
- ▶ Stripe kit
- ▶ Mulch kit
- ▶ High vacuum kit

* As rated by the engine manufacturer.

** Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

Kawasaki is a registered trademark owned by KAWASAKI JUKOGYO KABUSHIKI KAISHA. Vanguard is a registered trademark owned by Briggs & Stratton Corporation. Hydro-Gear is a registered trademark owned by Hydro-Gear Limited Partnership.