



SUPER 104

AVAILABLE DECK SIZES

Engine	Deck Sizes
38.5HP* - Kawasaki® FX1000 EFI	104"RD
40HP* - Vanguard® BIG BLOCK™ EFI w/ Oil Guard	104"RD



SUPER 104

SmoothTrak™ Steering

Precision control designed to help trim and maneuver easily around obstacles without feeling unstable or jerky.

HyperDrive® Hydro System

Features industrial-grade pumps and motors to handle tough jobs and long days.

I3M™ Suspension Seat

High-back seat with adjustable armrests and 3-inch travel range.

Commercial-Grade Engines

Vanguard® Big Block™ EFI with Oil Guard and FX1000 EFI engine options.

Hydraulic Deck Height Adjustment

Raising and lowering your cutting height is easy.

Hydraulic Wings

Easily raise and lower wings for transporting.



80" Transport Width

Fits most trailers helping to make it easy to transport from job-to-job.

104" Width of Cut

Widest and most productive commercial zero-turn available from Hustler Turf.



SUPER 104

- ✔ **104" Width of Cut**
Widest commercial zero-turn available from Hustler Turf.
- ✔ **80" Transport Width**
Fits most trailers helping to make it easy to transport from job-to-job.
- ✔ **HyperDrive® Hydro System**
- ✔ **Can mow a football field in under 10 minutes.**



ACCESSORIES

(Each sold separately)

- ▶ Mulch kit
- ▶ Steering lever extension kit
- ▶ Light kit
- ▶ Anti-scalp kit
- ▶ Flasher kit
- ▶ Beacon kit
- ▶ Flex Forks®
- ▶ Hitch kit
- ▶ Semi-pneumatic wheel/tire
15 x 6 Black



SUPER 104

ENGINE	Kawasaki FX1000 EFI (38.5hp)	Vanguard Big Block EFI (40hp)
MSRP	\$43,399	\$44,699
Contractor Pricing	\$34,719	\$35,759
ENGINE		
Manufacturer	Vanguard®, Kawasaki® FX series	
HP	104"RD deck: 38.5HP* - Kawasaki® FX1000 EFI 104"RD deck: 40HP* - Vanguard® BIG BLOCK™ EFI w/ Oil Guard (Per SAE J1995)	
Displacement	Vanguard® 993 cc, 999cc Kawasaki®	
Cooling	Air cooled	
Air Cleaner	Remote canister	
Engine Warranty	3 year limited	
DRIVE SYSTEM		
Type	Dual hydrostatic	
Pumps	Danfoss® DDC20	
Wheel Motors	Parker® TG	
Hydraulic Lines	Stainless steel Parker® Seal-Lok technology	
Reservoir Capacity	3 gallons	
Speed	Up to 11 mph	
Parking Brakes	Integrated with steering levers	
DECKS		
Cutting Width	Rear-discharge: 104"	
Cutting Heights	1" - 5.5"	
Deck Lift	Hydraulic powered	
Depth	5.5"	
Blades	5	
Blade Length	1 - 23.86" CW 1 - 23.86" CCW 1 - 20.50" CCW 2 - 20.50" CW	
Blade Tip Speed	Wing Decks: 15,800 • Center Deck: 15,500	
Spindles	Ductile cast iron with steel shafts and sealed ball bearings	
Drive	Electric PTO clutch	
Construction	11ga. welded steel	
Spindle Mounts	Reinforced 7ga. doubler	
Impact/Trim Areas	1.5" x .375" steel bar	
CONSTRUCTION		
Frame	1.5" x 3" steel tubing	
Front Axle	Fabricated with tapered roller bearings	
Front Caster Wheels	Tapered wheel bearings and debris cap	
Front Caster Forks	Fabricated 1/2" steel	
GENERAL		
Seat	I3M™ suspension seat, adjustable armrests and back	
Fuel Capacity	12 gallons	
Cupholder	Yes	
Front Tire	15 x 6.0 - 6	
Drive Tire	26 x 12 - 12	
Wing Tire	11 x 4 semi-pneumatic	
DIMENSIONS		
Weight	2500 lbs	
Height	54" • 71.5" w/ ROPs	
Length	95.5"	
Width	106.1" wings down, 80.0" wings up at gauge wheels, 72.5" wings up at deck base	
Tire Width	60.3"	
Trim Side	23.2"	
Specifications are subject to change without notice.		
PRODUCTIVITY**		
Acres Per Hour	9.24	

* As rated by the engine manufacturer.

** Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

Kawasaki is a registered trademark owned by KAWASAKI JUKOGYO KABUSHIKI KAISHA. Vanguard is a registered trademark owned by Briggs & Stratton Corporation.

Parker is a registered trademark owned by Parker Intangibles LLC. Danfoss is a registered trademark owned by Danfoss A/S.