



Tractors Made in BELARUS

MTZ 1220 (122 hp)

- Loaded with extra features as part of the standard package
- Heaviest tractor in its class, with largest 3 pt hitch capacity
- 4WD - Auto and full lockup modes
- Durable, reliable engine (no DEF, no DPF, no computers)
- Bar axle for rear wheels space adjustment
- PTO modes: 540/1000 / Ground speed / Disengaged
- Dedicated steering system
- Long stroke, low rev engine rated for 10,000+ hours
- Economical on fuel
- Service does not require any specialized tooling
- MTZ - World's largest exporter of Tractors



Heaviest tractor in its class with largest 3 pt hitch capacity



PTO modes: 540/1000 / Ground Speed / Disengage



Available with self-leveling loader

● Durable ● Reliable ● Affordable

• **Durable** • **Reliable** • **Affordable**

MTZ 1220

STANDARD FEATURES - MTZ 1220 Tractors come equipped with Cab including: AC, heater, joystick, inside & outside mirrors, front and rear windshield wipers • Dedicated steering system • Block heater • Lights included: headlights (hi & low beam), 4 front & 2 rear work lights, brake lights, turn indicators and 4 way flashers • 3 remote hydraulic valves (2 are joystick controlled) • Quick change PTO shaft • 4WD has 3 selections • Front and Rear radial tires • Front Fenders • Front weights + weight carrier • Air Compressor, for cleaning radiator in the field, inflating tires etc. • Complete PDI (Pre Delivery Inspection) - Field Ready

SPECIFICATIONS

Engine		Brakes	Oil immersed
Manufacturer	Minsk Motor Plant, Belarus		
Model	D-245.2S3AM		
Horsepower*	122 Engine 112 PTO		
Displacement	4.75L (290 cu. in.)		
Rated Speed RPM	2200		
Cylinder	4		
Diesel	Direct injection		
Aspiration	Turbocharged		
Air compressor + hose	Standard		
Electrical Equipment		Hydraulic System	Live, open centre, gear type pump
Alternator	12V 1,150 W	Pump Capacity	56 L/min (15 Gal./min)
Starter rated voltage	24 v, 5.500 W	Hydrostatic power steering	14 L.min (3.6 Gal./min)
Clutch	Dual, Dry Disk	Remote valves	3; 2 are Joystick controlled
Transmission		Draft control	Mechanical
Type	Synchronised Speed	3 point hitch	Category II with Linkage stabilizers
Gears	16 forward, 8 reverse	Lift capacity @ hitch point	4,300 kg (9,555 lb.)
Speed range	Forward: 1.8 to 42.7 km/h (1.1 to 26.5 mph) Reverse: 3.3 to 20.5 km/h (2.1 to 12.7 mph)		
4WD		Cab	Heat and Air Conditioning
Front Axle	Straight front axle	2 Doors	Flat Platform
Type	Planetary Spur Reduction Gears	Seat suspension	Mechanical
Control modes	Off / Always on / Automatic Safety clutch protection		Optional Grammer Seat
Rear Axle	Bar type		
Adjustable hubs	Tapered cone style		
Differential	Off / Always on / Automatic		
PTO		Capacities	
Type	Mechanical independent live	Fuel Tank	2 tanks 270 L (71 gal) or 1 tank 140 L (37 gal.)
Speeds	540/1000 / Ground speed	Hydraulic System	45 L (11.8 gal.)
Weights		Tires	
		Front	420 / 70R24
		Rear	18.4R38
Dimensions		Dimensions	
		Wheelbase	2.6 m (8.5')
		Overall Length	4.6 m (15.1')
		Height to Top of Cab	2.89 m (9.5')
		Clearance	0.63 m (2.1')
		Turning Radius	4.49 m (14.7')
		Fordable depth	0.85 m (2.8')
Weights		Weights	
		Weight (operational)	4,300 kg (12,170 lbs.)



Head Office: 3-1136 Centre St., Ste. 124, Thornhill, ON, L4J 3M8 Canada
Tel: 1-855-2GO-4MTZ (1-855-246-4689) Fax: 1-647-933-9066
E-mail: info@mtzequipment.com Web: www.mtzequipment.com

Warehouses: Canada - 2682 Highway 34, Hawkesbury, ON, K6A 2R2, Canada
USA - 2001 West Interstate 30, Sulphur Springs, TX, 75482, USA