

Rotary Cutter

SERIES	I		II			
	MODEL	418	518	528	628	728
Cutting width		48"	60"	60"	72"	84"
Cutting height		2" - 12"	2" - 12"	2" - 12"	2" - 12"	2" - 12"
Blade tip speed		13,098 ft/min	14,505 ft/min	16,371 ft/min	14,861 ft/min	14,369 ft/min
Spring steel blades		1/2" x 3" heat treated	1/2" x 3" heat treated	1/2" x 3" heat treated	1/2" x 3" heat treated	1/2" x 3" heat treated
Deck material		11 gauge	11 gauge	11 gauge	10 gauge	10 gauge
Gearbox		Closed (540 RPM)	Closed (540 RPM)	Closed (540 RPM)	Closed (540 RPM)	Closed (540 RPM)
Gearbox rating		40 hp	40 hp	60 hp	60 hp	65 hp
Tractor requirement		20 - 55 hp	20 - 55 hp	30 hp min	30 hp min	30 hp min
PTO shaft		Shear pin	Shear pin	Slip clutch	Slip clutch	Slip clutch
3-point hitch*		Category I	Category I	Category I	Category II	Category II
Tire - 3-point		15" laminated	15" laminated	16" solid rubber	16" solid rubber	20" solid rubber
Tire / wheels - trailing		N/A	N/A	Solid rubber or 15" rim	Solid rubber or 15" rim	15" rim
Stump-jumper		N/A	N/A	24" diameter	24" diameter	24" diameter
Parking jack		N/A	N/A	Optional	Optional	Optional
Chain kit		Optional	Optional	Optional	Optional	Optional
Weight - 3-point		448 lb	530 lb	680 lb	1037 lb	1175 lb
Weight - trailing		N/A	N/A	686 lb	856 lb	1476 lb