

7TH LIMITED YR INDUSTRY LEADING WARRANTY

HIKE

» HIGHLIGHTS

- Power-bar steering system – the easiest to learn, easiest to use walk-behind steering system
- Wide stance for increased stability
- 3.4 gal. fuel capacity
- Superior drive system – integrated, serviceable ZT2800 transmission
- No daily lube points
- 36", 48", 54" side-discharge decks



TOP SPEED

6.3
MPH

bigdogmowerco.com/hike

Visit your BigDog dealer for details.

Specifications subject to change without notice.



»SPECIFICATIONS

HIKE

DECKS

CUTTING WIDTH	36" 48" 54"
CUTTING HEIGHT	1.5" to 4.5"
DECK LIFT	Hand Operated
DEPTH	4"
BLADES	36" Deck: 2 48" Deck: 3 54" Deck: 3
BLADE LENGTH	36" Deck: 20.5" & 13.75" 48" Deck: 16.5" 54" Deck: 18.5"
SPINDLES	Aluminum w/ 1" steel shafts and sealed ball bearings w/ triple protection seals

DIMENSIONS

DECK SIZE	36"	48"	54"
HEIGHT	40.9"	40.9"	40.9"
LENGTH	75"	75"	76.1"
OVERALL WIDTH (with discharge chute up)	38"	50.4"	56.5"
WEIGHT	581 lbs.	660 lbs.	685 lbs.

GENERAL

FUEL CAPACITY	3.4 gal.
FRONT TIRE	11 x 4 - 5, smooth tread
DRIVE TIRE	36" Deck: 18 x 6.5 - 8, turf tread 48" Deck: 20 x 10 - 10, turf tread 54" Deck: 20 x 10 - 10, turf tread

ENGINE

MANUFACTURER	Kawasaki
HORSEPOWER	36" Deck: FS481 - 14.5 HP 48" Deck: FS541 - 15 HP 54" Deck: FS600 - 18.5 HP 54" Deck: FS691 - 23 HP (elec. start)
COOLING	Air Cooled, Fly-wheel fan
ENGINE WARRANTY	3 yrs.

DRIVE SYSTEM

TYPE	Dual Hydrostatic
TRANSMISSION	HydroGear ZT2800
SPEED	Forward: 0-6.3mph, Reverse: 0-2mph
PARKING BRAKES	Internal Transmission Mech. Brake

CONSTRUCTION

FRAME	1.5" x 2.0" x .120" steel
FRONT AXLE	Fabricated w/ steel ball bearings
FRONT CASTER WHEELS	Steel roller bearings
FRONT CASTER FORKS	Fabricated .375" steel on 36" Fabricated .5" steel on 48" & 54"