

## EXCAVATOR MULCHERS

# UMM/EX - UMM/EX/VT



from 130 to 300 L/min



Ø 30 cm max



from 20 to 30 t

## FORESTRY MULCHER WITH FIXED TOOTH ROTOR FOR EXCAVATORS.

The UMM/EX is the flagship model of the FAE excavator mulcher lineup. The larger dimension of the rotor gives a better performance with the option of choosing between various hydraulic motors and types of teeth. This model is extremely versatile and capable of meeting the requirements of all land reclamation professionals.

### STANDARD EQUIPMENT

Enclosed machine body
Belt transmission
Hydraulic piston motor 63cc with relief and anticavitation valve (UMM/EX) - (130 - 180 L/min)
110/60cc variable torque hydraulic piston motor (UMM/EX/VT) - (130 - 200 L/min)
Flow control valve
Hydraulic hood
Interchangeable counter blades
Motor enclosed in frame
Protection chains
Supporting service leg

### OPTIONS

Hydraulic piston motor 90cc with relief and anticavitation valve (UMM/EX) - (130 - 240 L/min)
160/115cc variable torque hydraulic piston motor (UMM/EX/VT) - (130 - 300 L/min)
Customized setting hydraulic motor (UMM/EX/VT)
Diverter valve
Additional reinforced side plates
Customized attachment bracket
Customized attachment bracket with fixed thumb
Multiple tooth options

## FEATURES



Enclosed machine body



Forged and hardened interchangeable counter-blades for the longest working life

Motor integrated into the frame protected from dirt and impact

Flow control valve protects the motor from excessive flow



## MAIN OPTIONS




1 Customized attachment bracket



2 Diverter valve to control the cylinders to control the opening and closing of the hydraulic door



3 Additional reinforced side plates for extreme conditions



4 VT motor Adjustable motor to obtain the maximum performance from any excavator

MODEL	Flow rate (L/min)		Pressure (bar)		Excavator weight (t.)		Working width (mm)	Weight (kg)	Max shredding diameter (mm)	No. teeth	
	min	max	min	max	min	max				C/3+C/3/SS	I+C/3/SS
UMM/EX 125	130	180	240	350	20	30	1340	1980	300	26+2	38+2
UMM/EX 150	130	180	240	350	20	30	1580	2080	300	32+2	46+2
UMM/EX/VT 125*	130	200	240	350	20	30	1340	1980	300	26+2	38+2
UMM/EX/VT 150*	130	200	240	350	20	30	1580	2080	300	32+2	46+2

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.  
\*Variable displacement hydraulic motor.



FOR THE MOST DEMANDING PROFESSIONALS  
IN THE MOST EXTREME CONDITIONS