

Unverferth® Grain Handling

30 Series Grain Wagons



High-Quality Grain Deserves A High-Quality Ride



Models 730, 630, 530

Performance, Convenience and Durability

Only Unverferth® grain wagons are designed and built with the **Innovative** Design and **Quality** Manufacturing characteristics of performance, convenience and durability! Unverferth grain wagons feature easy connections for convenient linking of units and are specifically designed to be pulled in tandem, fully loaded.



Performance

- All Unverferth high-capacity grain wagons feature the patented Ultra-Steer chassis. This specially designed frame means you can turn in a 40 percent tighter radius!
- Standard equipment four-wheel, surge-activated brakes on models 730 and 630 and two-wheel rear brakes on model 530 help ease the heaviest loads to a safe stop. Four-wheel brakes for model 530 are optional.
- Brakes automatically disengage when the wagon is backing up.
- The unloading chute is equipped with a center-dump deflector for pit unloading and the chute height is adjustable from 15" to 18". The metering door makes it easy to take grain samples for moisture and quality testing.
- Steep-sloped floors result in fast and complete unloading, up to 625 bushels in only 90 seconds.



Convenience

- The unloading door's rack-and-pinion mechanism with gear reduction allows for easy door opening, even when the box is full.
- The high-intensity lamp, located just above the unloading door, makes nighttime unloading as bright as high noon, and its on-off switch is built right into the light for operator convenience.
- Wagons that unload on the left side are standard. Right-side unloading is available as an option.
- All Unverferth high-capacity grain wagons feature a spring-lift-assist tongue and telescoping clevis hitch for easy, one-person hookup. There's also a standard equipment, heavy-duty transport chain for safer road travel.
- The front viewing ladder and front, rear and side windows make for easy checking of load contents.
- ASAE-approved, high-intensity LED flashing amber and red taillights, SMV emblem, seven-pin electric receptacle, rear hitch and welded-steel safety chain connector make tandem towing easier, safer and more convenient.
- Optional molded plastic fenders with mud flaps help protect the wagon finish from rock chips and other road debris. Fender sidemarker lights also improve nighttime transport visibility.
- Optional Weatherguard tarp with 18 oz. canvas keeps contents dry. The semi-trailer locking design provides optimum protection from the wind. Effortless roll-over operation is conveniently performed from the ground.
- All Unverferth high-capacity grain wagons can also be fitted with optional augers or conveyors for convenient handling of bulk seed or fertilizer.



Unverferth® Grain Handling

30 Series Grain Wagons



***High-Quality Grain
Deserves A High-Quality Ride***



Models 730, 630, 530

Unverferth® 30 Series Wagons



Heavy-duty spindles and hubs



Mesh-coated wiring



Torsion bar suspension



Durability

- Heavy-duty spindles and hubs provide years of dependable service.
- All wiring is mesh-coated and routed through conduit for extra protection and longer life.
- Unitized sidewall construction and the flame-cut one-piece end supports increase strength and capacity of Unverferth grain wagons.
- The sleek design also has fewer joints and seams that can rust, and all exposed seams are silicone-sealed for increased corrosion resistance.
- Your new Unverferth high-capacity grain wagon looks great when it arrives at your operation and will stay that way due to the full primer basecoat and a choice of tractor red or green high-gloss top coat for a car-like finish with increased durability.
- Torsion bar suspension and extra-wide, 42" runner spacings keep your wagons level and stable, even when going across the rows. Four-corner mounting keeps box chatter to a minimum, even when towing empty.

umequip.com

Specifications

Unverferth 30 series grain wagons specifications			
Model Number	730*	630*	530
Capacity (bushels)**	750	625	550
Length	17'7"	16'9"	15'7"
Width	9'6"	9'	9'
Height	10'8"	10'4"	10'
Front/Rear Slope	36°	37°	40°
Back Slope	32°	32°	32°
Door Width	60"	60"	60"
Chute Height	15" to 18"	15" to 18"	15" to 18"
Unloading Time	110 sec.	90 sec.	80 sec.
Spindle Size	3.5"	3.5"	3"
Hub Size	10-Bolt/11.25" BC	10-Bolt/11.25" BC	8-Bolt/8" BC
Wheel Size	13 x 22.5	13 x 22.5	13.5 x 22.5
Wheel Base	12'1"	11'5"	10'5"
Track Width	7'5"	7'5"	7'1"
Overall Tire Width	8'8"	8'8"	8'6"
Turning Radius	8'	6'	6'
Approx. Weight (lbs.)	7,180	6,760	5,700

*Please check local weight and towing regulations when pulling the 730 or 630 individually or in tandem.

** Capacities measured with #2 corn at 15% moisture (56 lb. test weight)

See your nearest Unverferth dealer today for complete details on all Unverferth grain wagons, visit our website at umequip.com or call 1-800-322-6301.

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.

Unverferth
Manufacturing Company, Inc.

P.O. Box 357 • Kalida, Ohio 45853
419.532-3121 • unverferth.com

Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. Unverferth Manufacturing Co., Inc., supports the efforts of Farm Safety 4 Just Kids and all other organizations that promote farm safety.

©2015 Unverferth Manufacturing Co., Inc. Printed in U.S.A.

®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH Patent#6176504
Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon and Canada



U30GW51021010M51