



BUSH HOG®

Performance You Can Count On™

RTG SERIES TILLERS



New for 2015

The gear driven “ROTO HOG” tillers by Bush Hog® are built Bush Hog® tough for years of dependable service. Available in standard or reverse till, there is a model that will fit your application. In ground cover conditions, a reverse till model works best because the flow of material tends to cover the chopped groundcover for quicker decomposition. The standard six blades per flange on every model gives the maximum breakup of soil even in hard or packed conditions. The heavy duty gear drive alleviates worries about the durability of a chain drive in the same tough conditions. The “ROTO HOG” is the perfect tool for landscape work, seed beds, or any other application that requires that the soil be pulverized.



Gear drive with oil bath in side gearbox is more durable than a chain drive that will wear and could break.



RT60GR
Rotary Tiller, 60-inches Model,
Gear Drive, Reverse Till

SPECIFICATIONS

Models	RT60G / RT60GR	RT72G / RT72GR	RT84G / RT84GR
Rotation	Standard / Reverse	Standard / Reverse	Standard / Reverse
Drivetrain	Gear	Gear	Gear
Hitch	ASAE Cat 1, Standard and Quick Hitch	ASAE Cat 1, Standard and Quick Hitch	ASAE Cat 1& 2, Standard and Quick Hitch
Working Width	59-inches	70 1/2-inches	82 1/2-inches
Total Width	66-inches	78-inches	90-inches
Number of Flanges	7	9	11
Blades per Flange	6	6	6
Rotor/Blade Rotation Diameter	17-inches	17-inches	17-inches
Rotor Shaft Diameter	3-inches	3-inches	3-inches
Rotor RPM	211	211	211
Weight	673-lbs. / 683-lbs.	747-lbs. / 759-lbs.	817-lbs. / 831-lbs.
PTO Driveline with Slipclutch	ASAE Cat4	ASAE Cat4	ASAE Cat4
Tilling Depth*	7 1/2-inches	7 1/2-inches	7 1/2-inches
Min / Max Tractor H.P. (PTO)	25 / 45	35 / 55	45 / 65
Colors	Available in Red, Orange, Blue and Green		

*Requires multiple passes

Dealer Info:



BUSH HOG®
Performance You Can Count On™

www.bushhog.com

Bush Hog®, Inc.
2501 Griffin Ave., Selma, AL 36703
(334) 874-2700

©June 2015 Bush Hog®, Inc.