



# **SNOW PRODUCTS**



**PTO  
Power Pack**

Models	SBLM66	SBLM76	SBLM86
<b>HP - Minimum</b>	40 HP	40 HP	40 HP
<b>Cutting Width</b>	66"	76"	86"
<b>Cutting Edge</b>	3/8" x 3"	3/8" x 3"	3/8" x 3"
<b>Skid Shoes</b>	3/8" x 1-1/2"	3/8" x 1-1/2"	3/8" x 1-1/2"
<b>Auger Tube</b>	3-1/2" OD	3-1/2" OD	3-1/2" OD
<b>Auger Flighting</b>	5/16 x 2-1/4	5/16 x 2-1/4	5/16 x 2-1/4
<b>Auger Diameter</b>	19"	19"	19"
<b>Roller Chain</b>	#60	#60	#60
<b>Hitch Plate</b>	Quick-tach	Quick-tach	Quick-tach
<b>Chute Rotation</b>	Hydraulic	Hydraulic	Hydraulic
<b>Chute Diameter</b>	12"	12"	12"
<b>Main Body Height</b>	31"	31"	31"
<b>Chute Deflector</b>	Hydraulic	Hydraulic	Hydraulic
<b>Fan Diameter</b>	26"	26"	26"
<b>Fan Depth</b>	8"	8"	8"
<b>Auger Drive</b>	Hydraulic	Hydraulic	Hydraulic
<b>Fan Drive</b>	Hydraulic	Hydraulic	Hydraulic

## Snow Blowers - Single Auger Models



MK Martin's Meteor series 3PH snowblowers are built to get your work off the ground with durable performance and high-capacity design. The Meteor is available in a range of models for 12 HP compact tractors to 175 HP farm tractors.

Models	SB46	SB54	SB60	SB68
<b>HP (Rec.)</b>	12 HP	15 HP	20 HP	30 HP
<b>Cutting Width</b>	46"	54"	60"	68"
<b>Cutting Edge</b>	1/4 x 1-1/2	3/8 x 1	3/8 x 1	3/8 x 1
<b>Auger Diam.</b>	10"	14"	14"	14"
<b>Fan Diam.</b>	17"	21"	21"	21"
<b>Chute Diam.</b>	5-1/2"	8"	8"	10"
<b>Chute Rotation (Man/Hyd)</b>	Std/Opt	Std/Opt	Std/Opt	Opt/Opt
<b>Chute Deflector (Man/Hyd)</b>	Std/NA	Std/Opt	Std/Opt	Std/Opt
<b>Main Body Height</b>	20"	25"	25"	29"
<b>3PH Mount</b>	CAT. 1	CAT. 1	CAT. 1	CAT. 1
<b>Weight (LBS.)</b>	268	366	396	506



Models	SB72	SB75	SB87	SB97
<b>HP (Rec.)</b>	35 HP	50 HP	60 HP	75 HP
<b>Cutting Width</b>	72"	75"	87"	97"
<b>Cutting Edge</b>	3/8 x 1	1/2 x 1-1/2	1/2 x 2	1/2 x 2
<b>Auger Diam.</b>	14"	15"	19"	19"
<b>Fan Diam.</b>	21"	23"	27"	27"
<b>Chute Diam.</b>	10"	10"	12"	12"
<b>Chute Rotation (Man/Hyd)</b>	Opt/Opt	Opt/Opt	Opt/Opt	Opt/Opt
<b>Chute Deflector (Man/Hyd)</b>	Std/Opt	Std/Opt	Std/Opt	Std/Opt
<b>Main Body Height</b>	29"	29"	36"	36"
<b>3PH Mount</b>	CAT. 1	CAT. 1 & 2	CAT. 2	CAT. 2
<b>Weight (LBS.)</b>	540	748	1,034	1,106

## Double Auger Models



Models	HP	RPM
<b>97D/108D</b>	100-125	540
<b>97D175/108D175</b>	125-175	540
<b>97D1.75/1081.75</b>	1 3/4 20 Tractor End	1,000
<b>97DF/108DF</b>	1 3/8 21 Tractor End	1,000
<b>SB120D</b>	150-200	540
<b>SB120 D 1.75</b>	1-3/4 20 Tractor End	1,000
<b>SB120DF</b>	1-3/8 21 Tractor End	1,000

Models	SB87D	SB97D	SB108D	SB120D
<b>HP (Rec.)</b>	60 HP	100 HP	125 HP	200 HP
<b>Cutting Width</b>	87"	97"	108"	120"
<b>Cutting Edge</b>	1/2 x 2	1/2 X 6*	1/2 x 6*	1/2 x 6*
<b>Auger Diam.</b>	15" (x2)	19" (x1) 15" (x1)	19" (x1) 15" (x1)	23" (x1) 15" (x1)
<b>Fan Diam.</b>	27"	32"	32"	36"
<b>Chute Diam.</b>	12"	13"	13"	13"
<b>Chute Rotation (Man/Hyd)</b>	Opt/Opt	NA/Std	NA/Std	NA/Std
<b>Chute Deflector (Man/Hyd)</b>	Std/Opt	Std/Opt	Std/Opt	Std/Opt
<b>Main Body Height</b>	36"	43"	43"	47"
<b>3PH Mount</b>	CAT. 2	CAT. 2 & 3	CAT. 2 & 3	CAT. 2 & 3
<b>Weight (LBS.)</b>	1,161	1,900	1,980	3,010
<b>Opt. 1000 RPM</b>	-	Yes	Yes	Yes

\*Bolt-on and reversible



## BACKDRAG SCRAPER (Optional)

- Hydraulic control
- Ideal for pulling that remaining snow away from your door
- Complete with corner markers

Models	SB68 P/T	SB75 P/T	SB87 P/T
<b>HP (Rec.)</b>	35 HP	50 HP	60 HP
<b>Cutting Width</b>	69"	75"	87"
<b>Cutting Edge</b>	3/8 x 1	1/2 x 1 1/2	1/2 x 2
<b>Auger Diam.</b>	14"	15"	19"
<b>Fan Diam.</b>	21"	23"	27"
<b>Chute Diam.</b>	10"	10"	12"
<b>Chute Rotation (Man/Hyd)</b>	Manual or Hydraulic (opt.)	Manual or Hydraulic (opt.)	Manual or Hydraulic (opt.)
<b>Chute Deflector (Man/Hyd)</b>	Std./Opt. 6" cyl.	Std./Opt. 8" cyl.	Std./Opt. 8" cyl.
<b>Main Body Height</b>	25"	29"	36"
<b>3PH Mount</b>	CAT. 1	CAT. 1 & 2	CAT. 2
<b>Weight (LBS.)</b>	671	748	1,034

## Meteor Features

### 3 Point Hitch / Quick Attach Compatible


All models are built standard with 3PH in CAT. 1 or CAT. 2, and are completely compatible with Quick Attach.



**3PH Mounts**

### High Tensile Steel Ribbon Flighting


To make sure you get the longest dependable service from your blower all Meteors have the highest quality High Tensile Steel Ribbon flighting on the auger providing strength to move the snow to the fan.



**Flighting**

### Four Blade Fan

The Meteor four blade fan is ruggedly designed and built to quickly and consistently blow the snow out of the chute.



**Four Blade Fan**

### 1000 RPM PTO Kit

Available on the 97 and 108 models, a kit is available to allow larger tractors to run at 1000 RPM PTO. The 1000 RPM Kit also raises the input shaft to allow the PTO shaft to run at a lesser angle on larger tractors increasing the efficiency and life of the driveline components.



**1000 RPM Kit**

### Gear Box

The heart of Meteor's power train is the time-proven Comer gearbox.



**Gear Box**



## Chute Rotator

Meteor Snow Blowers chute rotators come in manual (crank), hydraulic (orbital motor), and electric.



**Manual**  
(wormgear)



**Hydraulic**  
(orbital motor)



**Electric**

## Chute Deflector

Exit chute deflectors are available in manual or hydraulic (opt).



**Manual**



**Hydraulic**

## Multi Hinged Deflector (Optional)

Meteor's Multi Hinged Deflector provides you with finer control over where your snow is blown.



**\*Cylinder not included**

## Skid Shoes

Adjustable skid shoes are included with all snow blowers to protect your surface and your blower.



**Skid Shoes**





Meteor Snow Blowers for Skid Steer Loaders feature one piece side plate construction for added strength and rigidity. They also feature an offset chute for better operator vision.

- Hydraulic line check valve prevents reverse rotation and allows the motor to overrun after valve is shut off
- Heavy duty 12 volt electric chute rotator
- Direct fan drive mounted with 2" bearings
- Heavy duty fan has 5 impeller blades
- Optional Electric Chute Deflector

Models	SSB62	SSB66	SSB76	SSB86	SSB96
<b>Cutting Edge</b>	1/2 x 3	1/2 x 3	1/2 x 3	1/2 x 3	1/2 x 3
<b>Cutting Width</b>	62"	66"	76"	86"	96"
<b>Auger Diam.</b>	19"				
<b>GPM (min)</b>	14	14	14	30	30
<b>Mounting</b>	Universal Skidsteer Attach				
<b>Chute Rotation</b>	Hydraulic				
<b>Chute Diam.</b>	11"				
<b>Main Body Height</b>	31"				
<b>Chute Deflector (Man/Hyd)</b>	Std/Opt				
<b>Fan Diam.</b>	26"				
<b>Weight (LBS.)</b>	900	925	950	975	1,025

Flow Rates	Code	Flow Rates	Code
<b>14-17 GPM</b>	A	23-26 GPM	C
<b>18-20 GPM</b>	B	27-33 GPM	C+
<b>20-22 GPM</b>	B+	33-40 GPM	D

Code "C+" and "D" are high flow packages (have a bigger fan motor and uses the standard auger motor in series with flow control).

Code "D" high flow package is recommended on the SSB 96.