

SPECIFICATIONS FOR:

Walinga Pneumatic Grain Moving Unit Model 7816 DLX

SPECIFICATIONS:	7816 DLX	
HEIGHT	109" (277 cm)	
WIDTH	95" (241 cm)	
LENGTH	141" (358 cm)	
WEIGHT	5560 lbs (2522 kg)	
DISCHARGE HEIGHT	16.6'(5.1m) maximum - 8"(0.2m) minimum	
HP REQUIRED	150-180 hp	
PTO SPEED	1000 RPM	
LINE SIZE	7" (178 mm) only	
TIRES	Farm Implement (12.5L 15SL) 3420 lbs max load capacity	
WHEELS	12.5" (32 cm) Steel Rim / 6 bolt hub	
BLOWER	#816 Walinga SRT (Sound Reduction Type), Super Hardened Coating, Positive Displacement Blower	
AIRLOCK	#2018 cast iron shell, precision machined housing, 10 vane rotor, Hardox steel tips, hydraulically driven, reversible rotation	
DRIVE	Tongue mounted drive shaft with V-type 5 groove sheaves & belts	
HYDRAULICS	Self Contained	
RECEIVER	32" dia. (81 cm) two piece. Dual inlets. Rhino Lined	
PRECLEANER	23" dia. (58 cm)	
SAFETY	Vacuum/Pressure relief valves	

7816 DLX

CAPACITY*	Bu/hr*	Tonnes/hr*
Corn & Barley	5500	140
Wheat	5000	136
Soybeans	4800	131

*Capacities based on using 12' (3.65 m) suction line and truck loading kit. Capacity will vary with condition of product. Due to continuous product development, specifications are subject to change without notice. Some items shown may be optional

WALINGA", COM

Head Office Michigan

1190 Electric Ave. R.R. #5, Guelph, Ontario Wayland, Michigan USA 49348 Canada N1H 6J2 Tel: 519.824.8520 Tel: 616.877.3470 Tel: 888.925.4642 Tel: 800.466.1197 Fax: 519.824.5651 Fax: 616.877.3474

Manitoba

Suction Nozzle

> 70 3rd Ave. N.E. Box 1790 Carman, Manitoba Canada ROG 0J0 Tel: 204.745.2951 Fax: 204.745.6309

Ontario

938 Glengarry Cres. Fergus, Ontario Canada N1M 2W6 Tel: 519.787.VACS (8227) Fax: 519.787.8210

Australia

Customvac Australia 24 Molloy St. Toowoomba Qld 4350 Australia







Super Hardened Coating Airlock

STANDARD ACCESSORIES

- · Self contained hydraulics
- · Stainless steel delivery lines
- Dual inlets
- Hose carrier
- Precleaner
- · Walinga SRT (Sound Reduction Type) Positive Displacement Super Hardened Coating Blower
- · Hydraulic-rotating truck loading kit with cyclone
- Two 7" dia. x 12' (175 mm x 3.65 m) stainless steel delivery lines
- One 7" (175 mm) dia. suction nozzle
- One 7" dia. x 12' (175 mm x 3.65 m) rubber clean-up hose with swivel coupling
- One 7" (175 mm) dia. wheeled 'Backsaver' floor sweep nozzle attachment
- · Rhino liner covering high wear areas including full receiver tank and cyclone





