

COMPACT SMOOTHWALL SOLUTIONS

The compact Magnum G Smoothwall bin is designed for easy shipping, and even easier set up – configure them with the factory options specific to your operation and then simply drop them into place! Whether you're a grower looking to add some additional storage for your farm, craft brewery, distillery or feed operation – these bins are the perfect storage solution for small spaces.

KEY FEATURES

- Diameters available: 8' or 9' 6"
- Sidewall heights available: 8', 10', 12', 15'
- 60° cone for easier cleanout and less hangout
- Roof and sidewall ladders for easy access to roof and lid opening
- Large 24" roof lid opening for quick loading
- 19" bolt flange discharge for unload flexibility
- 34" tall discharge clearance for versatile unloading adaptations
- Sight glass above support ring for visibility inside the bin without having to climb up

SUITABLE FOR:

- Small farms
- Breweries
- Distilleries
- Feed operations

ADDITIONAL OPTIONS INCLUDE

- Welded foundations
- Weld on or bolt on rack and pinion assembly
- Roof inspection hatch
- Auger boots
- Transitions
- Auger mount tabs
- Lifting lugs
- Level alerts
- Additional sight glasses
- 8" poke holes
- 5" pail spouts
- Bottom inspection hatch
- Internal paint
- Option for flat deck shipping
- Roof vents
- Pneumatic fill tubes feed into roof, not lid
- PVC Fill/Vent pipes
- Ladder cages

AGI is a leading provider of equipment solutions for agriculture bulk commodities including seed, fertilizer, grain, and feed systems with a growing platform in providing equipment and solutions for food processing facilities. AGI has manufacturing facilities in Canada, the United States, the United Kingdom, Brazil, India and Italy and distributes its products globally.

Westeel Saskatoon #1 North Corman Industrial Park Saskatoon, Saskatchewan, S7K 3P5
800.667.1161 | 306.931.0066 | custservice.sask@westeel.com | aggrowth.com/westeel

AGGROWTH.COM aggrowthintl.com 



AGI  WESTEEL

WELDED SMOOTHWALL HOPPER BOTTOM BINS - NON-EPOXY LINED (60 DEGREE BOTTOM CONE)

Includes Sidewall & Roof Ladders, 24" Roof Opening (c/w spring lid), 19" Bolt Flange (34" clearance) & 1 x Sight Glass at Sidewall Bottom

PART NO.	MODEL NO.	GRAIN TONS	FEED TONS	CAPACITY (CU. FT.)	CAPACITY (BU.)	DIA.	OVERALL HEIGHT	EAVE HEIGHT	AUGER LENGTH	LBS. PER UNIT
8' DIAMETER BINS										
291548	808 MAG-G	16	12	566	478	8' 0"	19' 0"	16' 8"	36'	1,792
291549	810 MAG-G	19	14	667	562	8' 0"	21' 6"	19' 2"	41'	1,950
291550	812 MAG-G	22	16	767	647	8' 0"	23' 6"	21' 2"	41'	2,109
291551	815 MAG-G	27	19	918	775	8' 0"	26' 6"	24' 2"	46'	2,346
9' 6" DIAMETER BINS										
291552	908 MAG-G	24	18	841	710	9' 6"	21' 4"	18' 5"	36'	2,202
291553	910 MAG-G	28	21	983	829	9' 6"	23' 4"	20' 5"	41'	2,394
291554	912 MAG-G	32	24	1,124	949	9' 6"	25' 4"	22' 5"	41'	2,567
291555	915 MAG-G	39	28	1,337	1,128	9' 6"	28' 4"	25' 5"	46'	2,857

Note: The bulk density of grains and feeds will vary depending upon the blend and manufacturer. Westeel calculates the capacity by using 55 lb/cu. Ft for grain and 40 lb/cu. Ft for feed. Multiply the bulk density of the product you are storing by the cu. ft. capacity of the bin for an exact tonnage rating.

STEEL FOUNDATIONS

PART NO.	MODEL NO.	RECOMMENDED BIN SIZE	RING TUBES	LBS. PER UNIT
291597	FOUNDATION 8' BIN (1 RING)	808, 810, 812, 815	1 RING 6" x 4"	196
291600	FOUNDATION 9' BIN (1 RING)	908, 910, 912, 915	1 RING 6" x 4"	226

OPTIONS/ACCESSORIES

PART NO.	MODEL NO.	LBS. PER UNIT
SMALL BIN ACCESSORIES		
292007	R&P MS WELD STYLE SHORT - 8' & 9'6" BIN	30
291986	R&P ASM MS BOLT STYLE SHORT - 8' & 9'6" BIN	30
294433	INSTALL 19" TOP INSPEC. HATCH KIT (ROPE)	33
AUGER BOOT	AUGER BOOT C/W BOLT FLANGE - CALL FACTORY TO SPECIFY SIZE/DESIGN	
TRANSITION	DISCHARGE TRANSITION C/W BOLT FLANGE - CALL FACTORY TO SPECIFY SIZE/DESIGN	
2 IN 1 BOOT	COMBINATION AUGER BOOT AND SHUT OFF - BOLT ON	100
294419	INSTALL AUGER MOUNT TAB KIT	1
291367	INSTALL BIN LIFTING LUGS - SIDEWALL (2)	15
294408	INSTALL LEVEL ALERT KIT	1
294250	INSTALL SIGHT GLASS Ø6" KIT	1
294413	INSTALL 8" POKE HOLE	41
291806	INSTALL 5" PAIL SPOUT - 60° HOPPER KIT	47
291967	INSTALL BOTTOM INSPECTION HATCH 6"	23
FLAT DECK	KIT - INCLUDES ACCESSORIES TO SHIP BIN ON STEP DECK INSTEAD OF BIN SHIPPING TRAILER	0
PNT INT	INTERNAL PAINT COATING	0
SMALL BIN ROOF VENT OPTIONS		
290982	INSTALL CIRCVENT 23" ROOF VENT KIT (PVC)	5
291937	INSTALL GOOSENECK VENT (14"X14") ONE-WAY	80
290950	INSTALL GOOSENECK VENT (14"X14") TWO-WAY	46
PNEUMATIC FILL AND VENT OPTIONS		
291975	INSTALL PNEU FILL Ø4" 808-60° INTO ROOF	404
291976	INSTALL PNEU FILL Ø4" 810-60° INTO ROOF	557
291977	INSTALL PNEU FILL Ø4" 812-60° INTO ROOF	586
291978	INSTALL PNEU FILL Ø4" 815-60° INTO ROOF	608
291981	INSTALL PNEU FILL Ø4" 908-60° INTO ROOF	579
291982	INSTALL PNEU FILL Ø4" 910-60° INTO ROOF	601
291983	INSTALL PNEU FILL Ø4" 912-60° INTO ROOF	630
291984	INSTALL PNEU FILL Ø4" 915-60° INTO ROOF	672
298822	INSTALL PVC FILL VENT - 6" X 8' SIDEWALL	94
291997	INSTALL PVC FILL VENT - 6" X 10' SW VENT	101
298823	INSTALL PVC FILL VENT - 6" X 12' SW VENT	109
291905	INSTALL PVC FILL VENT - 6" X 15' SW VENT	119