

No Sprayer Delivers More

Jacto **A200/A200V** Airblast Sprayers

4-Way Control Valve

Conveniently located within operators reach. Glycerin-filled pressure gauge included.

Chemical Container Triple-Rinse System

Protects the operator and the environment.

16 Flip-Over Nozzle Holders

For rapid application rate changes or individual nozzle shutoff.

Fresh-Water Tank

For operator safety and chemical container triple rinse.

50-Gallon Poly Tank

UV resistant, high-density, polyethylene.

22-Inch Diameter Fan

Produces 12,065 cfm at 51 MPH.

Quick-Connect Fittings

Quickly attach/remove optional hand-spray guns.

Fan Disconnect

Reduces power consumption during spot spraying and agitation.

High-Pressure Piston Pump

11 GPM Ceramic cylinder JP-42 for long life and durability.

Jacto offers a complete line of trailed Airblast sprayers up to 1,000 gallon capacity.



Arbus 500

jacto[®]
No Sprayer Delivers More

Jacto A200 airblast sprayers deliver big performance in a small package. Filled with features that ensure long life, excellent durability, and maximum crop protection for hobby farmers and small growers, Jacto designed the A200 to economically meet the demands of orchard, vineyard, Christmas tree, berry, and other fruit and nut applications. Specially designed for compact tractors working in tight areas.

A200/A200V Airblast Sprayers

Jacto A200/A200V

Cat# A200010803 ©2003, Jacto, Inc.
Photo shown for reference only. Actual sprayer may vary.



Specifications

Jacto A200/A200V Airblast Sprayers

| | | |
|-------------------|---|---------------------------------|
| Weight | Without Deflector - A200 | 375 lbs. |
| | With Deflector - A200V | 410 lbs. |
| Dimensions | Length | 50 in. |
| | Width Without Deflector - A200 | 40 in. |
| | Width With Polyethylene Deflector - A200V | 72 in. |
| | Height | 45 in. |
| Tank | Capacity | 50 gal. |
| | Material | Polyethylene |
| Filter | Model | FVS-100 |
| | Mesh | 60 |
| Pump | Model | JP-42 |
| | Capacity | 11 gpm |
| | Power Consumption | 1.9 hp |
| | Piston Quantity | 3 |
| Control | Model | CJ-42A |
| Nozzles | Nozzle Type | JA-2 / JA-4 |
| | Quantity Without Deflector - A200 | 16 |
| | Quantity With Deflector - A200V | 14 |
| | Maximum Working Pressure | 300 psi |
| Agitation | | Bypass With Venturi |
| Deflector Options | A200 | Steel Vertical Deflector |
| | A200V | Polyethylene Vertical Deflector |
| Fan | Diameter | 22 in. |
| | Rotation | 2,035 rpm |
| | Air Volume | 12,065 cfm |
| | Air Speed | 51 mph |
| | Power Consumption | 4.6 hp |

Additional Equipment Specifications

| | |
|--|----------|
| Maximum PTO Speed | 540 rpm |
| Maximum Power Consumption | 6.5 hp |
| Minimum Recommended Tractor | 18 hp |
| Minimum Required 3-Point Lift Capacity | 900 lbs. |
| Recommended Maximum Working Speed | 3.7 mph |



9650 SW Herman Rd
Tualatin, Oregon 97062

Tel: 800.522.8610 Fax: 800.511.3671
Web: www.jacto.com Email: info@jacto.com

Specifications subject to change without notice.