

# 1550 SERIES FIVE SECTION DISC HARROWS



**Model SF1550-50**  
Five Section Flexibility



3-Row Heavy Duty  
Coil Tine Harrow (optional)



Thirty Plus Acres Per Hour



Models in 47' & 50' Widths

## SF1550 SERIES FIVE SECTION DISC



Duplex wing hinges (patent pending) provide the wings with two pivot points. The lower pivot, closer to the blades, allows more down flex (10°) than competitive five section tools (5° to 7°). In addition, it maintains proper blade spacing. The upper pivot provides the offset needed to fold the wing frames for transport.

### Big, Acre Eating Appetite Manages Over Thirty Acres Per Hour With Five Section Flexibility

Over 600 pounds per foot equals 230 plus pounds per blade to cut through the toughest crop residue and penetrate the hardest of soils.



Disc gang control is augmented by a gauge wheel on each wing. The gauge wheels are designed into the disc harrow and are located near the outside ends of the disc gangs for optimum gang control. Vertical adjustments are made with parallel linkage keeping constant the angle of the wheel arm to the soil. The gauge wheels pivot on maintenance free UHMW bushings.

Moving from field to field is easy and stress free thanks to the narrow width and low transport dimensions of the SF1550 series tandem disc harrows.



Walking Triple Tandems (pat. pen.) located in the center section have 50% more weight carrying capacity than conventional walking tandems. A total of fourteen tires supply unequalled flotation and implement carrying capacities.

## 1550 SERIES FIVE SECTION DISC HARROWS

MODEL NUMBER	WORKING WIDTH FT. (m.)	BLADE SPACING (mm) & BLADE SIZE	IMPLEMENT CARRIAGE	WEIGHT lbs. (kg.)	WEIGHT PER FOOT lbs. (kg.)	TRANSPORT WIDTH ft. (m.)	TRANSPORT HEIGHT ft. (m.)
SF1550-47	47' (14.33) 24' (609.60)	8.75" (222.25)	Center (6) 12.5L (GY-FI-F) tires with 15x10 wheels and 8 bolt, 2.75" hubs. Wings (8) 12.5L, 12 ply tubeless tires with 15x10 wheels and 6 bolt 2" hubs.	31,302 (14,199)	666 (302)	18' 2" (5.54)	13' 11" (4.25)
SF1550-50	50' (15.24)	24" (609.60)	Center (6) 12.5L (GY-FI-F) tires with 15x10 wheels and 8 bolt, 2.75" hubs. Wings (8) 12.5L, 12 ply tubeless tires with 15x10 wheels and 6 bolt 2" hubs.	33,300 (15,105)	666 (302)	18' 2" (5.54)	13' 11" (4.25)

FOR MORE INFORMATION:  
1-800-525-4384 • Email: AGCOanswers@agcocorp.com  
Internet - www.sunflowermfg.com



Sunflower Manufacturing Co., Inc.  
P.O. Box 566 • 3154 Hallie Trail • Beloit, KS 67420