


# ARBUS 270



**THE ARBUS 270** is an excellent sprayer. It will give you good coverage at a very competitive price. Its components are light and resistant: a thick wall high density polyethylene tank, steel tubes, ceramic nozzles with individual shut-off valve, and single three way control valve with regulator. It can be mounted on a small tractor to spray blueberries, apples, pears, cherries, grapes, plums, vegetable crops, turf, nursery stock and Christmas trees.



# SMALL SIZE - GREAT PERFORMANCE



## One Way Volute (optional)

It is made of fiberglass and mounted on the left side.

Its movable head allows spraying at different angles. This will be good, thorough coverage.

## TECHNICAL SPECIFICATIONS

**Tank:** 70 gallon tank. Equipped with a basket strainer, it has level sight, drain plug and special hydraulic agitation system which provides mixing even with a small return volume.


**Filter:** The ARBUS 270 sprayer is equipped with a main filter on the inlet line. Fixed directly to the tank, it has shut-off valve to facilitate cleaning operations even with a full tank. Its 60-mesh screen minimizes plugging.

**Pump:** The Jacto piston JP-50 with 15 GPM capacity was developed to work under the most rigorous conditions. Its ceramic sleeves, stainless steel valves and reinforced crankshaft ensure maximum wear, chemical resistance and the precise application rate you need.

**Control unit:** Mounted within the operator's reach with pressure gauge. Brass body and ceramic valve provide the maximum hardness gauge regulation. Only one lever for all operations: right side, left side, both sides and return. A two-way valve placed on the lower end of the right boom enables use of the hand gun with no need to disconnect any hose from the control unit, thus avoiding parts wear.

**Nozzles:** Five adjustable nozzles on each boom. Equipped with ceramic (alumina) tips and whirl plate, a 30-mesh filter and a shut-off valve on the back.

**Fan:** It has a 24.5 in diameter aluminum hub with two-position plastic blades adjustable according to your tractor's horsepower. When you use a gun or mix the chemicals the fan can be disengaged.



MÁQUINAS AGRÍCOLAS JACTO S.A.

Rua Dr. Luiz Miranda, 1650 - C.P. 35

17580-000 - Pompéia - SP - Brasil

Tel.: 55 14 3405 2100 - Fax: 55 14 452 1306

E-mail: [impex@jacto.com.br](mailto:impex@jacto.com.br)