

FARMALL® C SERIES COMPACT TRACTORS SPECIFICATIONS

CASE II
AGRICULTURE



FARMALL® C SERIES COMPACT TRACTORS SPECIFICATIONS

Introducing a new line of Tier 4 B/Final compliant premium tractors with more fuel capacity to run longer with less harmful emissions.

- Larger operator's platform offers easier access and exit
- Deluxe seat features adjustable backrest, armrests and mounts on an inclined plane for taller operators
- Same excellent all-around visibility from the operator's seat
- Improve rear visibility to drawbar, PTO & 3-point hitch
- Larger 17.5L-24 R4 industrial tire offering on Class 3 models
- Improved control layout and placement
- Easy routine maintenance
- Attachment bundles for specific applications

FARMALL C SERIES SPECIFICATIONS	FARMALL 30C	FARMALL 35C	FARMALL 40C	FARMALL 50C
ENGINE				
Type	Tier 4 B/Final			
Gross Horsepower	33 hp (24 kW)	37 hp (27 kW)	41 hp (30 kW)	47 hp (34 kW)
Rated Speed, RPM	2600 rpm			
No. of Cylinders	3		4	
Aspiration	Turbo		Natural	
Displacement	91 cu in. (1.5 L)		135 cu in. (2.2 L)	
Air Cleaner	Replaceable dry element			
Fuel Tank	10.5 gal. (40 L)			
Alternator	85 amps			
PTO				
PTO HP, Gear/Hydro	26/24.7	29.6/28.1	32.4/30.8	37.3/35.4
PTO Speed	540 RPM			
PTO Type	Independent with electro-hydraulic engagement			
Mid-PTO Speed	2000			
TRANSMISSION				
Type, Mechanical/Hydrostatic	12x12/HST +3 range		16x16/HST +3 range	
Maximum Forward Speed, Gear, MPH (kph), R4	14.2 mph (22.9 kph)		17.0 mph (27.3 kph)	
HST, MPH (kph), R4	14.8 mph (23.8 kph)		17.9 mph (28.8 kph)	
Gear/shuttle type	Synchro			
Rear Diff. Lock Engagement	Mechanical			
Brake Type	Wet, multi disc			
HYDRAULICS				
Implement Hydraulic Flow	8.2 gal. (31.0 lpm)			
Steering Hydraulic Flow	4.2 gal. (15.9 lpm)/5.3 gal. (19.9 lpm) HST			
Remote Valves	Optional			
3-Point Lift Capacity @ Ball End	1,807 b. (820 kg)		2,756 b. (1 250 kg)	
3-Point Linkage Category	1			
Steering Type	Hydrostatic			
DIMENSIONS				
Wheel Base	66 in. (167 cm)		73 in. (185 cm)	
Length	122 in. (310 cm)		129 in. (328 cm)	
Width	61 in. (155 cm)		69 in. (175 cm)	
Height	93.5 in. (237.5 cm)		96.5 in. (245 cm)	
Weight	3,137 in. (1 423 cm)		3,945 in. 1 789 cm)	

Specifications are subject to change without notice.

CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2014 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Printed in U.S.A. www.caseih.com

Form number: CIH02061401