

HLA *ROOT RAKE & STONE FORK*



LEAVE NO [**STONE
ROCK
BRANCH
ROOT**] **UNTURNUED**



Rocky Starts **STRONG FINISHES**




Stone Fork Kverneland Tines

- 39" Conus II cranked Kverneland tines (32" useable length)
- 18 Cranked Tines
- Tines installed on 4" centres
- Ruggedly built
- Heavy 3 lbs grating on back

Part#	Tines	Weight
SF60	18-Cranked Tines	610 lbs
SF72	21-Cranked Tines	690 lbs
SF84	24-Cranked Tines	770 lbs
SF96	27-Cranked Tines	850 lbs
SF108	30-Cranked Tines	935 lbs
SF120	34-Cranked Tines	1,035 lbs

The HLA Stone Fork provides an easy way to clean up rocks and debris while allowing soil and fine materials to sift through. With an available model and duty rating to accommodate most equipment, HLA Stone Forks can be used in nearly any industry from landscaping professionals to next generation farmers, and industrial earth moving applications.

For increased versatility the Stone Fork can be equipped with the HLA Utility Grapple or the HLA Split Grapple.



Take on **ROOT, ROCK, & DEBRIS**



The Root Rake is designed to be invaluable for cleanup operations and is ideal for quickly gathering debris. Afterward the debris can be cleared with an added grapple.

Regular duty Root Rakes can be equipped with dual independent grapples providing a firm grasp on even the most awkward loads.

The flame cut tines are spaced so you can pick up what you want and leave behind what you don't. The digging points are made of 400 Brinell High Tensile Steel for longer life and better digging ability.

1.866.567.4162

Stone Fork (Compact Duty)

- 1" Shaft diameter
- 2½" spacing between tines
- Points are 5/8" thick, 400 Brinell high strength steel
- 23" High
- 35" Deep
- 2,000 lbs capacity

Stone Fork (Regular Duty)

- 1¼" Shaft diameter
- 2½" spacing between tines
- Points are 5/8" thick, 400 Brinell high strength steel
- 23" High
- 40" Deep
- 5,500 lbs capacity

Stone Fork (Heavy Duty)

- 1¾" Shaft diameter
- 2¾" spacing between tines
- Points are 3/4" thick, 400 Brinell high strength steel
- 31" High
- 44" Deep
- 9,500 lbs capacity

Part#	Tines	Weight
SFRC48	Retainer Tines	410 lbs
SFRC55	Retainer Tines	450 lbs
SFRC62	Retainer Tines	490 lbs
SFRC70	Retainer Tines	530 lbs

Part#	Tines	Weight
SFR55	Retainer Tines	570 lbs
SFR62	Retainer Tines	630 lbs
SFR70	Retainer Tines	690 lbs
SFR77	Retainer Tines	745 lbs
SFR84	Retainer Tines	805 lbs
SFR92	Retainer Tines	865 lbs

Part#	Tines	Weight
SFRH77	Retainer Tines	1,225 lbs
SFRH85	Retainer Tines	1,345 lbs
SFRH90	Retainer Tines	1,405 lbs
SFRH94	Retainer Tines	1,465 lbs
SFRH98	Retainer Tines	1,525 lbs
SFRH103	Retainer Tines	1,585 lbs
SFRH108	Retainer Tines	1,650 lbs



Root Rake (Light Duty)

- Light weight and rugged design for compact loaders
- 28" overall height with grapple closed
- 7 3/8" centre to centre tine spacing
- Points are 1/2" thick, commercial steel
- Available with or without single full width grapple

Part#	Description	Weight
RRLD48	48" (No Grapple)	260 lbs
RRGLD48	48" (With Grapple)	385 lbs
RRLD54	54" (No Grapple)	280 lbs
RRGLD54	54" (With Grapple)	410 lbs
RRLD60	60" (No Grapple)	305 lbs
RRGLD60	60" (With Grapple)	445 lbs
RRLD66	66" (No Grapple)	325 lbs
RRGLD66	66" (With Grapple)	470 lbs

Root Rake

- Regular duty
- 34" overall height with grapple closed
- 7 3/8" centre to centre tine spacing
- Points are 1/2" thick, 400 Brinell high tensile steel
- Available with or without dual independent grapples for complete clamping on awkward loads

Part#	Description	Weight
RR66	66" (No Grapple)	580 lbs
RRG66	66" (With Grapple)	985 lbs
RR78	78" (No Grapple)	670 lbs
RRG78	78" (With Grapple)	1,070 lbs
RR88	88" (No Grapple)	720 lbs
RRG88	88" (With Grapple)	1,125 lbs
RR96	96" (No Grapple)	790 lbs
RRG96	96" (With Grapple)	1,200 lbs

LIMB SAW



ALSO AVAILABLE



Manure Fork



Log Grapple



Side Discharge



Free Stall Scraper



2 Prong Spear



8082 Road 129, R.R.#3, Listowel, ON, Canada N4W 3G8
Tel. (519) 291-4162 | Toll Free (866) 567-4162
Fax (519) 291-5388 | sales@horstwelding.com

www.horstwelding.com

Authorized Dealer