

Auger Tubes & Flighting

Along with our plastic augers, MARKET FARM EQUIPMENT offers replacement plastic tubes for a number of our competitor's steel augers.

These plastic auger tubes allow you to use most of your augers existing parts like the flighting, hopper, hoses, winch, motor/valve and in most cases even the downspout.

Standard lengths are 12', 14' & 15'.

Plastic tubes available for the following steel augers:

Market 612, 120 Pivot Style
 J&M Pivot Style, Uni-Swivel
 Turnco 12T4, 14T4
 Killbros 110, 112, 114, 115
 Unverferth/McCurdy AG-12, AG-14

Flighting available (top driven)

5-5/8" straight blade plastic
 5" cupped plastic
 5-5/8" cupped steel
 5-5/8" bristle tipped
 7" cupped plastic
 7-1/2" straight blade plastic
 7-1/2" cupped steel
 7-1/2" bristle tipped

Lengths available:

12', 14', 15', 18', 20' & 25'
 12', 14', 15', 18', 20' & 25'
 12', 14', 15', 18', 20' & 25'
 12', 14', 15', 18', 20' & 25'
 12', 14', 15', 18', 20' & 25'
 12', 14', 20' & 25'
 12', 14', 20' & 25'
 12', 14', 15', 18', 20' & 25'



GRAVITY BOX AUGERS

ULTRA-GLIDE AUGER



Optional hopper fits doors up to 60" wide.

*Optional brackets for gravity boxes with straight door side.

The ULTRA-GLIDE AUGER's unique plastic hopper design allows the spout to remain pointing downward as the auger is moved from side to side. This allows for proper flow.

Available in 6" & 8" dia. x 12', 14' & 15' lengths.

MARKET FARM EQUIPMENT LTD.

RR#1 DASHWOOD, ONTARIO, CANADA, N0M 1N0
 TEL# 519-238-2301 FAX# 519-238-6044

E-MAIL: mfeltd@execulink.com
 WEB-SITE: www.marketfarmequipment.com

"SERVING THE FARM INDUSTRY SINCE 1962"

OLD FAVORITES

PIVOT AUGER



The PIVOT AUGER has a bottom pivot pin & pan style hopper design.

The advantage of this hopper design is high ground clearance.

Optional adaptor brackets for boxes with straight door side.

Available in 6" dia. x 12', 14' & 15' length.

The auger is 10½" lower than the door when in transport.

Optional wing extension kit for the pivot style hopper fits doors up to 60" wide.

Optional telescoping & rigid downspouts



SWIVEL AUGER



The SWIVEL AUGER has a sump design.

The hopper moves up & down with the auger when raised.

The advantage of this hopper design is maximum ground clearance.

Mounts equally well on gravity boxes with a sloped or straight door side.

Optional hopper fits doors up to 60" wide.

Available in 6" & 8" dia. x 12', 14' & 15' lengths

The auger is 2" lower than the door when in transport.

Standard features:
Sch. 40 PVC tube, 6 cu. inch motor c/w manifold mount control valve, 1000 lb. brake winch, 4' wire reinforced downspout, ½" x 22' hydraulic hoses, adjustable transport bracket, EZ-Swing cable system & choices of plastic, cupped plastic, bristle & cupped steel flighting.



"AUGER-MATE" HYDRAULIC POWER UNIT