




- Excavated material is uniformly distributed to the right side 10 to 20 (33 ft - 66 ft) meters or the deflector can be adjusted to deposit the materials forming a bank at the edge of the ditch.**

- La terre travaillée est expulsée du rotor sur la droite de la machine à une distance de 10 à 20 mètres; un coffre réglable permet de former un andain sur le bord du fossé.**

- Il terreno viene espulso sul lato destro della macchina, ad una distanza variante da 10 a 20 m; l'apposito cofano registrabile consente di accumularlo sul bordo del fosso.**

- Die ausgehobene Erde wird zur rechten Seite ausgeworfen, in der Weite von 10 bis 20 m. Die verstellbare Haube erlaubt die Ablegung in Form eines Dammes.**

- El terreno es expulsado por el lado derecho de la máquina a una distancia variable de 10 a 20 metros; la pantalla regulable permite acumularlo en el borde de la zanja.**



MOD.		HP	rpm		Kg.	Lbs.	A		B		C	
							cm	inches	cm	inches	cm	inches
SM-2 45		40 - 50	540	329	281	618	45	18"	72	29"	18	7"
SM-2 55		45 - 65	540	329	298	655	55	22"	90	36"	24	10"
SM-2 45 - S		40 - 50	540	329	315	693	45	18"	72	29"	18	7"
SM-2 55 - S		45 - 65	540	329	332	730	55	22"	90	36"	24	10"

Technical data are subject to change and not binding.



SOVEMA SPA
Via Olmo 6 - 14100 Gaggio di Piano - Italy
Phone +39 059 938585
Fax 059 938512
E MAIL: Sovema@sovema.com
WEB site: http://www.sovema.com
Factories: Gaggio di Piano - Arzago

SOVEMA Inc.
1937 Vanderhorn DR.
Memphis TN 38134
Phone 901 388 8348
Fax 901 388 8349
E MAIL: Sovema@sovemausa.com
WEB site: http://www.sovemausa.com

SOVEMA CANADA LTD.
4845 Portage Avenue
Headingley Manitoba R4H 1C7
Phone 204 897 6975
E MAIL: Sovema@sovemacanada.com
WEB site: http://www.sovemacanada.com