

# Offset Disc - 8550

| Model                     | 8550  |
|---------------------------|---|
| <b>Blade Spacing</b>      | <b>14" (356 mm)</b>   |
| Width, working            | 9.5' to 15.5' (2.9 to 4.7 m)  |
| Width, transport          | 2.5' (762 mm) wider than working width  |
| Weight, per foot          | 1050 lb (476 kg)  |
| Weight, per blade         | 636 lb (288 kg)   |
| Horsepower required*      | 20 to 25 DBHP/ft  |
| <b>Structure</b>          |   |
| Frame                     | 10" x 4" x 0.5" (254 x 102 x 13 mm)   |
| Gang beam size            | 10" x 4" x 0.5" (254 x 102 x 13 mm)   |
| Hitch, length             | 92" (2.33 m), floating hitch  |
| Hanger, standard          | Rigid, U-Bolt Mounted   |
| Gang shaft                | 1-15/16" (49 mm)  |
| Spools                    | Steel fabricated c/w locking drive lug half spools                                    |
| Bearings                  | T2-215 series trunnion mounted, regreaseable, 22,800 lb (10342 kg) radial load rating |
| Gang angle                | 25°, 22° F & R  |
| <b>Blades</b>             |   |
| Blade sizes, notched      | 32" x 1/2" (813 x 12 mm)  |
| <b>Features</b>           |   |
| Adjustable rigid scrapers | 4" x 3/4" (102 x 19 mm) steel   |
| Tires                     | 12.5 L x 15 FI  |
| Depth control             | Single 4" x 12" (102 x 305 mm) hydraulic cylinder c/w depth control segments          |

\*Depends on working depth, soil type, field speed, etc.