

## Offset Disc - 1225 / 1275

Model	1225		1275	
Blade Spacing	9" (230 mm)	10.5" (267 mm)	10.5" (267 mm)	12" (305 mm)
Width, working	10' to 15' (3 to 4.6 m)	6' to 20' (1.8 to 6.1 m)	6' to 20' (1.8 to 6.1 m)	6' to 20' (1.8 to 6.1 m)
Width, transport	2.5' (762 mm) wider than working width		2.5' (762 mm) wider than working width	
Weight, per foot	603 lb (274 kg)	565 lb (256 kg)	630 lb (286 kg)	651 lb (295 kg)
Weight, per blade	242 lb (110 kg)	266 lb (121 kg)	297 lb (135 kg)	340 lb (154 kg)
Horsepower required*	5 to 6 DBHP/ft	7 to 8 DBHP/ft	7 to 9 DBHP/ft	7 to 9 DBHP/ft
<b>Structure</b>				
Frame	6" x 4" x 3/8" (152 x 102 x 8 mm)	6" x 4" x 3/8" (152 x 102 x 8 mm)	8" x 4" x 3/8" (203 x 102 x 8 mm)	8" x 4" x 3/8" (203 x 102 x 8 mm)
Gang beam size	6" x 4" x 3/8" (152 x 102 x 8 mm)	6" x 4" x 3/8" (152 x 102 x 8 mm)	6" x 4" x 3/8" (152 x 102 x 8 mm)	6" x 4" x 3/8" (152 x 102 x 8 mm)
Hitch, length	92" (2.33 m)	92" (2.33 m)	92" (2.33 m)	92" (2.33 m)
Hanger, std.	Rigid, U-Bolt Mounted	Rigid, U-Bolt Mounted	Rigid, U-Bolt Mounted	Rigid, U-Bolt Mounted
Hanger, opt. stone flex	1.25" x 2.5" (32 x 64 mm)	1.25" x 2.5" (32 x 64 mm)	1.25" x 2.5" (32 x 64 mm)	1.25" x 2.5" (32 x 64 mm)
Gang shaft	1-15/16" (49 mm)	1-15/16" (49 mm)	1-15/16" (49 mm)	1-15/16" (49 mm)
Spools, steel fabricated	5-1/2" (140 mm) Dia. O.D.	5-1/2" (140 mm) Dia. O.D.	5-1/2" (140 mm) Dia. O.D.	5-1/2" (140 mm) Dia. O.D.
Bearings	410 WSS series	410 WSS / T2-215 series	T2-215 series trunnion mounted, regreaseable, 22,800 lb radial load rating	
Gang angle	25°, 22°, 19° F & R	25°, 22°, 19° F & R	25°, 22°, 19° F & R	25°, 22°, 19° F & R
<b>Blades</b>				
Blade sizes, notched/smooth	24" x 5/16" (610 x 8 mm)	24" x 5/16" (610 x 8 mm)	26" x 5/16" (660 x 8 mm)	26" x 5/16" (660 x 8 mm)
Blade sizes, optional, smooth	24" x 5/16" (610 x 8 mm) 26" x 5/16" (660 x 8 mm)	-	-	-
Blade sizes, optional notched/smooth	26" x 5/16" (660 x 8 mm)	26" x 5/16" (660 x 8 mm) 26" x 3/8" (660 x 9 mm) 28" x 3/8" (711 x 9 mm)	26" x 3/8" (660 x 9 mm) 28" x 3/8" (711 x 9 mm) 30" x 3/8" (762 x 9 mm)	26" x 3/8" (660 x 9 mm) 28" x 3/8" (711 x 9 mm) 30" x 3/8" (762 x 9 mm)
<b>Features</b>				
Adjustable rigid scrapers	4" High Carbon Steel	4" High Carbon Steel	4" High Carbon Steel	4" High Carbon Steel
Tires	11L x 15 FI	11L x 15 FI	11L x 15 FI	11L x 15 FI
Depth control	Single 4" x 12" (102 x 305 mm) hydraulic cylinder c/w depth control segments			

\*Depends on working depth, soil type, field speed, etc.