

EG5000



- Economical, portable power with traditional Honda durability and performance
- 5,000 watts maximum AC output
- Home stand-by and Commercial usage (for non-GFCI applications)
- Suitable for rental applications



SPECIFICATIONS

GENERATOR TYPE	BRUSH TYPE	TRANSPORT WHEELS	OPT. (P/N 06710-Z22-A40ZA)
MAXIMUM AC OUTPUT (WATTS)	5000	LIFTING HOOK	OPT. (P/N 06810-Z22-A30ZA)
VAC VOLTAGE AVAILABLE	120 / 240	BATTERY	N/A
MAXIMUM CONTINUOUS AC OUTPUT (WATTS)	4500	APPROXIMATE RUNNING TIME / TANKFUL (HRS.)	7.5** / 11.0****
MAX. RATED AC AMPERAGE @ 120 V / 240 V	37.5 / 18.8	RATED FUEL CONSUMPTION (LITRES / HOUR)	3.22**
GROUND FAULT CIRCUIT INTERRUPTER (GFCI)	-	NOISE LEVEL (DBA) (1.5 METRES TO 7 METRES)	73**
FREQUENCY (HERTZ)	60	LENGTH (WITHOUT HANDLES AND WHEELS)	681 mm (26.8 in.)
AUTOMATIC VOLTAGE REGULATOR	STD. DIGITAL (DAVR)	LENGTH (WITH HANDLES AND WHEELS)	-
DC OUTPUT (VOLTS / AMPS)	-	WIDTH (WITHOUT HANDLES AND WHEELS)	530 mm (20.9 in.)
ENGINE TYPE	Honda GX390T2, OHV, 4-STROKE, AIR-COOLED	WIDTH (WITH HANDLES AND WHEELS)	-
DISPLACEMENT	389 cc	HEIGHT (WITHOUT LIFT-HOOK)	571 mm (22.5 in.)
STARTING SYSTEM	MANUAL RECOIL	HEIGHT (WITH LIFT-HOOK)	-
LOW LEVEL OIL ALERT™ SYSTEM	STD.	DRY WEIGHT	77.5 kg (170.9 lb)
AUTO THROTTLE	-	COLD CLIMATE TECHNOLOGY	STD.
REMOTE START CAPABILITY	NO	COMMON DUPLEX RECEPTACLE SPECIFICATIONS	37.5 amps / 120 VAC continuous is available as combined total from these two AC receptacles. Maximum of 18.8 amps available from each single receptacle.
REMOTE START KIT PART NUMBER INFO	-	DC RECEPTACLE SPECIFICATIONS	-
FUEL TANK CAPACITY (LITRES)	24	DC CHARGING CABLE	N/A
		HIGH CAPACITY 120/240 AC TWIST LOCK RECEPTACLE SPECS	This receptacle will supply 30 amps at 120 VAC continuously. This receptacle will supply 18.8 amps at 240 VAC continuously and 37.5 amps at 120 VAC.

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice.

See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.