

EU2000i



- 2000 watts of Honda inverter 120 VAC power
- Reliable Honda GX100T OHC four-stroke engine
- Whisper-quiet operation — 59 dB(A) at rated load, 53 dB(A) at 25% load
- Light construction projects, camping, boating, street vendors, operating lights, stand-by power source



SPECIFICATIONS

GENERATOR TYPE	INVERTER	TRANSPORT WHEELS	N/A
MAXIMUM AC OUTPUT (WATTS)	2000	LIFTING HOOK	N/A
VAC VOLTAGE AVAILABLE	120	BATTERY	N/A
MAXIMUM CONTINUOUS AC OUTPUT (WATTS)	1600	APPROXIMATE RUNNING TIME / TANKFUL (HRS.)	3.4** / 9.0***
MAX. RATED AC AMPERAGE @ 120 V / 240 V	13.3 / -	RATED FUEL CONSUMPTION (LITRES / HOUR)	0.97**
GROUND FAULT CIRCUIT INTERRUPTER (GFCI)	N/A	NOISE LEVEL dB(A) (1.5 METRES TO 7 METRES)	59** / 53***
FREQUENCY (HERTZ)	60	LENGTH	512 MM (20.2 IN.)
AUTOMATIC VOLTAGE REGULATOR	STD.	LENGTH - WITH HANDLES FOLDED	N/A
DC OUTPUT (VOLTS / AMPS)	12 / 8.0	LENGTH - WITH HANDLES	N/A
Honda ENGINE	GX100T	WIDTH - WITHOUT HANDLES AND WHEELS	290 MM (11.4 IN.)
TYPE	OHC; 4-STROKE; AIR-COOLED	WIDTH - WITH WHEELS	N/A
DISPLACEMENT	98.5 CC	HEIGHT - WITHOUT LIFT-HOOK	425 MM (16.7 IN.)
STARTING SYSTEM	MANUAL RECOIL	HEIGHT - WITH LIFT-HOOK	N/A
LOW LEVEL OIL ALERT™ SYSTEM	STD.	DRY WEIGHT	20.7 KG (45.6 LB)
AUTO THROTTLE	ECO-THROTTLE™ STD.	LENGTH - WITHOUT HANDLES AND WHEELS	N/A
REMOTE START CAPABILITY	NO	LENGTH - WITH HANDLES AND WHEELS	N/A
REMOTE START KIT PART NUMBER INFO	N/A	WIDTH - WITH HANDLES AND WHEELS	N/A
FUEL TANK CAPACITY (LITRES)	3.6	COLD CLIMATE TECHNOLOGY	YES

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice.

See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.