



500U

Forestry mulcher for special built hydraulic or PTO driven Prime Movers with power range between 250 and 500 HP.

Standard equipment: double side transmission, hydraulic hood, adjustable skids.

Options: customized hydraulic or PTO transmission, pushing frame, hydraulic pushing frame, customized attachment plate, teeth on hydraulic hood, possibility to have the rotor equipped with tooth type "C/SD" or type "A/SR".



500U

Model	Power HP Min - Max	Requirements		Working width inches	Overall width inches	Weight lbs rotor type C	Weight lbs rotor type B	Grinding diameter inches (max)	Teeth q.ty	
		Flow gal/min Min - Max	Pressure PSI Min - Max						A+C/SS	C+C/SS
500/U - 200	250 - 500	150 - 190	3500 - 5000	82	100	7916	8421	20	78+2	40+2
500/U - 225	260 - 500	150 - 190	3500 - 5000	91	110	8313	8800	20	88+2	44+2
500/U - 250	270 - 500	150 - 190	3500 - 5000	101	119	8710	9195	20	96+2	48+2

The data refers to the machine without options. Technical datas for models with mechanical transmission upon request.



Tooth type A



Tooth type C



Tooth type A/SR (option)



Tooth type C/SD (option)



Tooth type C/SS (side scraper)