

Unverferth® Tillage

Rolling Leveler Model 75



Primary tillage partner *for smooth secondary tillage*

The Unverferth Rolling Leveler is the ideal soil-finishing partner to pull behind your primary tillage tool. Its 16" diameter reels feature five spiraled, 3/8" x 3" beveled-edge blades for breaking up clods, knocking dirt off rootballs, smoothing residue and leveling ridges for a more receptive spring tillage trip. Save time, fuel and engine hours for lowering your input costs.

Model 75, 12' - 27' widths

Rolling Leveler primary tillage partner for a more receptive spring tillage trip

- Available in 12', 15' and 18' rigid and 18', 20', 22', 25' and 27' folding models
- 16" diameter reels with five, $\frac{3}{8}$ " x 3" beveled-edge blades for ideal leveling and better cleanout in heavier soils or wetter conditions
- Spiraled-blade design keeps blades in contact with soil surface for optimum leveling with minimal vibration
- Rugged 4" x 6" main frame and wing construction for added life
- Heavy-duty, 4-bolt flange bearing with full-length $1\frac{3}{4}$ " diameter shaft for long-term dependability
- 4"x 4" telescoping tongue retracts for easier storage and easy attachment to the lead implement
- Height-adjustable, reversible single-tang/double-clevis hitch for easy hitching to lead tool
- Top-winding, drop-leg jack for easy parking and a storage position for in-field use
- 3,000 p.s.i. hydraulics complete with hoses and endcaps for keeping hydraulic fluid cleaner
- Single hydraulics for raising and folding standard on folding models; dual split hydraulics optional
- Standard 9.5 x 15 transport wheels and available bolt-on dual wheel option
- SMV emblem, reflective markers and safety chain are standard equipment for enhanced transport safety
- Optional lighting package provides additional visibility for safer nighttime road travel
- Available in powder-coat finish of tractor red or green
- Horsepower requirements of $1\frac{1}{2}$ – 2 per working foot
- Optional wing-fold lockout valve for use with single hydraulics that disengages wing fold during field operation



Rigid and folding models



Drop-leg jack for easy parking and storage



4-bolt flange bearing with $1\frac{3}{4}$ " shaft for durability

For complete details on the Unverferth Rolling Leveler and all Unverferth tillage tools, see your nearest Unverferth dealer today, check our website at www.unverferth.com or call 1-800-322-6301.

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.



Manufacturing Company, Inc.
P.O. Box 357 • Kalida, Ohio 45853
(419) 532-3121 • FAX (419) 532-2468
unverferth.com
1-800-322-6301

Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. Unverferth Manufacturing Co., Inc., supports the efforts of Farm Safety 4 Just Kids and all other organizations that promote farm safety.

©2011 Unverferth Manufacturing Co., Inc. Printed in U.S.A.

®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH
Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon and Canada

