

TILT DECK TRAILERS



YEAR WARRANTY

Unmatched Two-Year Bumper-to-Bumper Warranty on all components. Five-Year Structural Warranty. *Ask us for details*.

FLEXIBLE FINANCING

Custom financing solutions available to best suit your business.

Ask us for details.

HITCH TYPE

PowerPin™ Ball GVWR 12,000 – 16,500 lb

20 Feet, 22 Feet

DECK LENGTH

RATED PAYLOAD 8900 -13,000 lb

Loads Faster.

Brandt Work Ready™ tilt deck trailers deliver fast loading and unloading to maximize your output. Their patent-pending Lode N Lok™ auto-latching decks save you valuable time while increasing operator safety.

1 Easier to Own

Brandt trailers are backed by the best support in the business to make ownership stress-free:

- Flexible purchasing options include rentals, rental purchasing, leasing, and conventional financing.
- Coast-to-coast 56-branch support network ensures parts and service are easily accessible, anywhere in Canada.
- Reliable design and long-lasting components reduce total cost of ownership.

2 Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Lode N Lok[™] self-locking deck enables faster loading, saving valuable time.
- Torsion spring suspension system delivers reliable shock-absorption without requiring any maintenance work.

(3) Safer

Safety is critical on the jobsite, so these models are designed with key features to maximize operator protection:

- Power PinTM ball hitch is specially designed to prevent binding, ensuring that the trailer is properly secured to the towing vehicle, every single time.
- Foolproof locking mechanism automatically secures the deck once the equipment is loaded, maximizing safety.
- Forward self-adjusting brakes keep the brakes at their peak performance for longer while eliminating the need for manual adjustments.



TILT DECK TRAILER SPECIFICATIONS

INDUSTRIAL TRAILER QUICK REFERENCE CHART	UBT620 - T	UBT620 - Tandem Tilt		UBT822 - Tandem Tilt	
Base Unit Key Specifications	PERF	PREM	PERF	PREM	
RELIABILITY - RATED CAPACITY					
GVWR (lb)	120	000	16000	16500	
Rated Payload (lb)	89	00	12500	13000	
Tongue Weight (lb)	16	00	20	00	
Axle Type (Bolt On)	Tors	Torsion		Torsion	
Axle Rating (lb)	2 x 5	2 x 5200		2 x 7000 2 x 8000	
Max Weight on Fixed Deck (lb)	10	1000		2000	
DURABILITY - STRUCTURE					
HSS Mainframe Size (in)	6	6 8			
Decking Material		Premium Fir			
Paint Finish	Polyuret	Polyurethane Primer + Hi-Gloss Polyurethane Paint, Rockguard			
DIMENSIONS					
Total Length (ft)	25	25.7		27.7	
Fixed Deck Length (ft)	4	4		6	
Tilt Deck or Tail Length (ft)	1	16		16	
Deck Width (in) - (inside fender to fender)	81	81.5		82.5	
Deck Height (in)	2	2	2	5	
INCLUDED EQUIPMENT					
Hitch Type		PowerPin	™ Ball - 2 5/16"		
Jackleg Wind Type - Top or Side	To	Тор		Side	
Jackleg Speeds	Sin	Single		Single	
Jackleg Lift Capacity (lb)	70	7000		10000	
Cushion Cylinder		•		•	
Steel Tread Plate Fenders (Bolt On)					
Wheel Size	15" Rim - 6 stu	15" Rim - 6 stud - 6.5" circle		17.5" rim - 8 stud - 6.5" circle	
Tire Size	ST225/75	ST225/75R15 LRE		ST235/80R16 LRE, ST215/75R17.5LRH	
EASY TO OPERATE - SAFETY & CONVENIENCE FEATURES					
Dual Chains c/w hook latches - 36"					
4" D-Rings		•		•	
Arctic Cold Weather Wiring		•		•	
Breakaway Switch (Includes LED test lights, battery & charger)		•		•	
Integral Footholds		•		•	
Lode N Lok Deck (Tilt Models)		•		•	
Tier 1 LED Lighting System		•			
Premium Radial 10 ply Tires (Speed Rated to 120 kph)			•		
Premium Radial 16 ply Tires (Speed Rated to 120 kph)				•	
Forward Self-Adjusting Brakes					
EZ-Lube Grease Axle Bearings					
Deck Traction Aid - Expanded Steel Mesh	0	•	•	•	
Heavy Duty Toolbox	0	•	•	•	
Black (Silver for Dual) Steel Wheels	•		•	•	
Aluminum Wheels	0	0	0	0	
ADDITIONAL FEATURES					
Tie Down Kit - 4x5000 lb WLL Chains c/w hooks, 4 ratchet	C	0		0	
Mud Flaps	0	0	0	0	
Pallet Fork Holders			0	•	
Spare Tire Carrier	0	•	0	•	
Spare Tire	0	•	0	•	