

Ready to Roll.

There's no time for downtime when you've got a job to do. Brandt **Work Ready**™ ramp deck trailers utilize a tried-and-true design with fewer moving parts to ensure they're always ready when you are.

1 Easier to Own

Brandt trailers are backed by the best support in the business to make ownership stress-free:

- Flexible purchasing options include rentals, rental purchasing, leasing, and conventional financing.
- Coast-to-coast 56-branch support network ensures parts and service are easily accessible, anywhere in Canada.
- Reliable design and long-lasting components reduce total cost of ownership.

Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Dual rear ramps are spring assisted, reducing strain on the operator while making loading and unloading quick and easy.
- Straightforward design utilizes fewer moving parts, increasing uptime and profitability.

Safer

Safety is critical on the jobsite, so these models are designed with key features to maximize operator protection:

- Rugged slipper spring suspension system is optimized to safely distribute weight between axles when carrying heavy loads on uneven ground.
- Premium fir decking provides better traction for the operator in wet and frozen conditions.
- Forward self-adjusting brakes keep the brakes at their peak performance for longer while eliminating the need for manual adjustments.



RAMP DECK TRAILER SPECIFICATIONS

INDUSTRIAL TRAILER QUICK REFERENCE CHART	UGF	UGR1124		UPR1124	
Base Unit Key Specifications	PERF	PERF PREM		PERF PREM	
RELIABILITY - RATED CAPACITY					
GVWR (lb)	22000	25000	22000	23000	
Rated Payload (lb)	15300	18040	15900	16600	
Tongue Weight (lb)	5	5000		3000	
Axle Type (Bolt On)		Equalized Leaf Spring			
Axle Rating (lb)	3 x 7000	2 x 10000	3 x 7000	2 x 10000	
DURABILITY - STRUCTURE					
Frame Size (in)		12" l-	Beam		
Decking Material		Premium Fir			
Surface Finish		Polyurethane Primer + Hi-Gloss Polyurethane Paint, Rockguard or Hot-Dipped Galvanized Finish			
DIMENSIONS					
Total Length (ft)	3	38.4		35.1	
Fixed Deck Length (ft)		24		24	
Tilt Deck or Tail Length (ft)		5		5	
Deck Width (in) - (inside fender to fender)	1	102		102	
Deck Height (in)	3	35.5 35.4			
INCLUDED EQUIPMENT					
Hitch Type	Goos	Gooseneck		Pintle	
Jackleg Wind Type - Top or Side	S	Side		Side	
Jackleg Speeds	D	Dual		Dual	
Jackleg Lift Capacity (lb)	20	20000		20000	
Tire Size	ST235/8	ST235/80R16 LRE ST235/8			
EASY TO OPERATE - SAFETY & CONVENIENCE FEATURES					
Spring Assist Full Width Beavertail Ramp - 4' x 5'		•		•	
Dual Chains c/w hook latches - 36"		•		•	
Arctic Cold Weather Wiring		•		•	
Breakaway Switch (Includes LED test lights, battery & charger)		•		•	
Integral Footholds (with handholds on Gooseneck models)		•		•	
Tier 1 LED Lighting System		•		•	
Premium Radial 10 ply Tires (Speed Rated to 120 kph)		•		•	
Forward Self-Adjusting Brakes		•		•	
EZ-Lube Grease Axle Bearings (oil bath bearings on 10,000 lb axles)		•		•	
Heavy Duty Toolbox	•	•	•	•	
Black Wheels	•		•		
Silver Wheels		•		•	
ADDITIONAL FEATURES					
Tie Down Kit - 4x5000 lb WLL Chains c/w hooks, 4 ratchet		0		0	
Mud Flaps	0	0	0	0	
Additional Storage Tray	•	•			
Spare Tire Carrier	•	•	•	•	
Spare Tire		•	•		