



UGR1124 / UPR1124

# RAMP DECK TRAILERS



## INDUSTRY BEST WARRANTY

### 2 YEAR WARRANTY

Unmatched Two-Year Bumper-to-Bumper Warranty on all components. Five-Year Structural Warranty. *Ask us for details.*

### FLEXIBLE FINANCING

Custom financing solutions available to best suit your business. *Ask us for details.*

#### HITCH TYPE

**PowerPin™  
Pintle,  
Gooseneck**

#### GVWR

**22,000 –  
25,000 lb**

#### DECK LENGTH

**24 Feet**

#### AXLE

**Triple,  
Tandem Dual**

## Ready to Roll.

There's no time for downtime when you've got a job to do. Brandt Work Ready™ ramp deck trailers utilize a tried-and-true design with fewer moving parts to ensure they're always ready when you are.

### ① Easier to Own

Brandt trailers are backed by the best support in the business to make ownership stress-free:

- Flexible purchasing options include rentals, rental purchasing, leasing, and conventional financing.
- Coast-to-coast 56-branch support network ensures parts and service are easily accessible, anywhere in Canada.
- Reliable design and long-lasting components reduce total cost of ownership.

### ② Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Dual rear ramps are spring assisted, reducing strain on the operator while making loading and unloading quick and easy.
- Straightforward design utilizes fewer moving parts, increasing uptime and profitability.

### ③ Safer

Safety is critical on the jobsite, so these models are designed with key features to maximize operator protection:

- Rugged slipper spring suspension system is optimized to safely distribute weight between axles when carrying heavy loads on uneven ground.
- Premium fir decking provides better traction for the operator in wet and frozen conditions.
- Forward self-adjusting brakes keep the brakes at their peak performance for longer while eliminating the need for manual adjustments.

Powerful Value. **Delivered.**

**Brandt**

# RAMP DECK TRAILER SPECIFICATIONS

| INDUSTRIAL TRAILER QUICK REFERENCE CHART                       |  | UGR1124<br>Tridem Ramp |                                | UPR1124<br>Tridem Ramp |                              | UGR1124<br>Dually Ramp |                       | UPR1124<br>Dually Ramp |      |
|--|--|------------------------|--------------------------------|------------------------|------------------------------|------------------------|-----------------------|------------------------|------|
| Base Unit Key Specifications                                   |  | PERF                   | PREM                           | PERF                   | PREM                         | PERF                   | PREM                  | PERF                   | PREM |
| RELIABILITY - RATED CAPACITY                                   |  |                        |                                |                        |                              |                        |                       |                        |      |
| GVWR (lb)  | 22000  |                        | 22000                          |                        | 25000                        |                        | 23000                 |                        |      |
| Rated Payload (lb)   | 15500  |                        | 15700                          |                        | 18800                        | 18300                  | 17100                 | 16900                  |      |
| Tongue Weight (lb)   | 5000   |                        | 3000                           |                        | 5000                         |                        | 3000                  |                        |      |
| Axle Type (Bolt On)  | Equalized Leaf Spring  |                        |                                |                        | Equalized Leaf Spring - Dual |                        |                       |                        |      |
| Axle Rating (lb)   | 3 x 7000   |                        |                                |                        | 2 x 10000                    |                        |                       |                        |      |
| DURABILITY - STRUCTURE   |  |                        |                                |                        |                              |                        |                       |                        |      |
| HSS Mainframe Size (in)  | 12   |                        |                                |                        |                              |                        |                       |                        |      |
| Decking Material   | Premium Fir  |                        |                                |                        |                              |                        |                       |                        |      |
| Paint Finish   | Polyurethane Primer + Hi-Gloss Polyurethane Paint, Rockguard |                        |                                |                        |                              |                        |                       |                        |      |
| DIMENSIONS   |  |                        |                                |                        |                              |                        |                       |                        |      |
| Total Length (ft)  | 38   |                        | 35.1                           |                        | 38                           |                        | 35.1                  |                        |      |
| Fixed Deck Length (ft)   | 24   |                        | 24                             |                        | 24                           |                        | 24                    |                        |      |
| Tilt Deck or Tail Length (ft)                                  | 5  |                        | 5                              |                        | 5                            |                        | 5                     |                        |      |
| Deck Width (in) - (inside fender to fender)                    | 102  |                        | 102                            |                        | 102                          |                        | 102                   |                        |      |
| Deck Height (in)   | 35   |                        | 35                             |                        | 38                           |                        | 38                    |                        |      |
| INCLUDED EQUIPMENT   |  |                        |                                |                        |                              |                        |                       |                        |      |
| Hitch Type   | Gooseneck  |                        | PowerPin™ Pintle               |                        | Gooseneck                    |                        | PowerPin™ Pintle      |                        |      |
| Jackleg Wind Type - Top or Side                                | Side   |                        | Side                           |                        | Side                         |                        | Side                  |                        |      |
| Jackleg Speeds   | Dual   | Dual                   | Single                         | Dual                   | Single                       | Dual                   | Single                | Dual                   |      |
| Jackleg Lift Capacity (lb)                                     | 20000  |                        | 20000                          |                        | 20000                        |                        | 20000                 |                        |      |
| Wheel Size   | 16" rim - 8 stud - 6.5" circle                               |                        | 16" rim - 8 stud - 6.5" circle |                        | Dual Rim 8 Stud- 6.5"        |                        | Dual Rim 8 Stud- 6.5" |                        |      |
| Tire Size  | ST235/80R16 LRE  |                        | ST235/80R16 LRE                |                        | ST235/80R16 LRE              |                        | ST235/80R16 LRE       |                        |      |
| EASY TO OPERATE - SAFETY & CONVENIENCE FEATURES                |  |                        |                                |                        |                              |                        |                       |                        |      |
| Spring Assist Partial Width Beavertail Ramp - 2' x 6'          |  |                        |                                |                        |                              |                        |                       |                        |      |
| Spring Assist Full Width Beavertail Ramp - 4' x 6'             |  |                        |                                |                        |                              |                        |                       |                        |      |
| Dual Chains c/w hook latches - 36"                             |  |                        |                                |                        |                              |                        |                       |                        |      |
| Arctic Cold Weather Wiring                                     |  |                        |                                |                        |                              |                        |                       |                        |      |
| Breakaway Switch (Includes LED test lights, battery & charger) |  |                        |                                |                        |                              |                        |                       |                        |      |
| Integral Footholds (with handholds on Gooseneck models)        |  |                        |                                |                        |                              |                        |                       |                        |      |
| Tier 1 LED Lighting System                                     |  |                        |                                |                        |                              |                        |                       |                        |      |
| Premium Radial 10 ply Tires (Speed Rated to 120 kph)           |  |                        |                                |                        |                              |                        |                       |                        |      |
| Forward Self-Adjusting Brakes                                  |  |                        |                                |                        |                              |                        |                       |                        |      |
| Super Lube Easy Grease Axle Bearings                           |  |                        |                                |                        |                              |                        |                       |                        |      |
| Deck Stop  |  |                        |                                |                        |                              |                        |                       |                        |      |
| Heavy Duty Toolbox   |  |                        |                                |                        |                              |                        |                       |                        |      |
| Open Top or Mesh Tray  |  |                        |                                |                        |                              |                        |                       |                        |      |
| Black (Silver for Dual) Steel Wheels                           |  |                        |                                |                        |                              |                        |                       |                        |      |
| Aluminum Spoke Wheels  |  |                        |                                |                        |                              |                        |                       |                        |      |
| ADDITIONAL FEATURES  |  |                        |                                |                        |                              |                        |                       |                        |      |
| Tie Down Kit - 4x5000 lb WLL Chains c/w hooks, 4 ratchet       |  |                        |                                |                        |                              |                        |                       |                        |      |
| Mud Flaps  |  |                        |                                |                        |                              |                        |                       |                        |      |
| Chain Rack (Gooseneck Models)                                  |  |                        |                                |                        |                              |                        |                       |                        |      |
| Spare Tire Carrier   |  |                        |                                |                        |                              |                        |                       |                        |      |
| Spare Tire   |  |                        |                                |                        |                              |                        |                       |                        |      |