

Road Warrior.

The Brandt Work Ready[™] 15-ton ramp deck trailer delivers superior capacity to get your equipment where it's going, every single day. This rugged model works as hard as you do, while taking all the punishment you can dish out.

1 Easier to Own

Brandt trailers are backed by the best support in the business to make ownership stress-free:

- Flexible purchasing options include rentals, rental purchasing, leasing, and conventional financing.
- Extensive coast-to-coast dealer network ensures parts and service are easily accessible, anywhere in Canada.
- Reliable design and long-lasting components reduce total cost of ownership.

Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Full-width ramps accommodate any kind of equipment without hassle, ensuring superior versatility.
- Dual two-speed 10,000 lb jacks are included as standard equipment to make coupling an uncoupling trailer effortless.

Safer

Safety is critical on the jobsite, so these models are designed with key features to maximize operator protection:

- Optional undercarriage toolbox, lower side step, and hydraulic ramps allow operators to work safely.
- Dependable 15,000 lb axles ensure positive hitch weight distribution and overall stability when hauling concentrated heavy payloads.
- Premium fir decking provides better traction for the operator in wet and frozen conditions.



15-TON TRAILER SPECIFICATIONS

INDUSTRIAL TRAILER QUICK REFERENCE CHART	UGR1526 Tandem Dualies	
Base Unit Key Specifications	PERFORMANCE	PLATINUM
RELIABILITY - RATED CAPACITY		
GVWR (lb)	30,000	
Rated Payload (lb)	21,600	21,200
Tongue Weight (lb)	6000	6000
Axle Type – bolt on	Equalized Leaf Spring - Dual	
Axle Rating (lb)	2 x 15000	
DURABILITY - STRUCTURE		
HSS Mainframe Size (in)	W14X22,50W	
Decking Material	Premium Fir	
Paint Finish	Polyurethane Primer + Hi-Gloss Polyurethane Paint	
DIMENSIONS		
Total Length (ft)	40.5	
Fixed Deck Length (ft)	26	
Tilt Deck or Tail Length (ft)	5.8	
Deck Width (in) – inside fender to fender	102	
Deck Height (in)	39.5	
INCLUDED EQUIPMENT		
Hitch Type	Gooseneck	
Jackleg Wind Type – top or side	Side	
Jackleg Speeds	Dual	Dual
Jackleg Lift Capacity (lb)	20,000	20,000
Wheel Size	Dual Rim 8 Stud - 275mm circle	
Tire Size	ST215/75R17.5 LRH	
Premium Radial 16 ply Tires – speed rated to 120 kph		
Corded Pump Remote		•
Mud Flaps		
EASY TO OPERATE - SAFETY & CONVENIENCE FEAT	URES	
Spring Assist Full Width Beavertail Ramp – 4' x 6'	•	
Hydraulic Full Width Beavertail Ramp – 8' x 6'		•
Dual Chains c/w Hook Latches – 36"		
Arctic Cold Weather Wiring		
Breakaway Switch – includes LED test lights, battery & charger		
Integral Footholds – with handholds on Gooseneck models		
Underbody Toolbox		•
Tier 1 LED Lighting System		
Forward Self-Adjusting Brakes		
EZ-Lube Grease Axle Bearings		
110V Shore Charging Plug In		•
Black (Silver for Dual) Steel Wheels		
HD Charge Kit		0
Wireless Pump Remotes		0
Spare Tire & Carrier	0	•