

Built to Pull Through.

Brandt Work Ready[™] ramp deck trailers are built with heavy-duty square tube frames, maximizing service life. And, their premium fir decking is denser and lasts longer than other decking options for superior reliability.

1 Easier to Own

Brandt trailers are backed by the best support in the business to make ownership stress-free:

- Flexible purchasing options include rentals, rental purchasing, leasing, and conventional financing.
- Coast-to-coast 56-branch support network ensures parts and service are easily accessible, anywhere in Canada.
- Reliable design and long-lasting components reduce total cost of ownership.

② Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Dual rear ramps are spring assisted, reducing strain on the operator while making loading and unloading quick and easy.
- Torsion spring suspension system delivers reliable shock-absorption without requiring any maintenance work.

Safer

Safety is critical on the jobsite, so these models are designed with key features to maximize operator protection

- Power PinTM ball hitch is specially designed to prevent binding, ensuring that the trailer is properly secured to the towing vehicle, every single time.
- Premium fir decking provides better traction for the operator in wet and frozen conditions.
- Forward self-adjusting brakes keep the brakes at their peak performance for longer while eliminating the need for manual adjustments.



RAMP DECK TRAILER SPECIFICATIONS

INDUSTRIAL TRAILER QUICK REFERENCE CHART	UBR820 - Tan	UBR820 - Tandem Ramp		UGR820 - Tandem Ramp	
	PERF	PREM	PERF	PREM	
RELIABILITY - RATED CAPACITY					
GVWR (lb)	16000		16800		
Rated Payload (lb)	11500		12000		
Tongue Weight (lb)	2000	2000		2800	
Axle Type (Bolt On)	Torsic	Torsion		Torsion	
Axle Rating (lb)	2 x 70	00	2 x 7000		
DURABILITY - STRUCTURE					
HSS Mainframe Size (in)	10		10		
Decking Material		Premium I		n Fir	
Paint Finish	Polyureth	Polyurethane Primer + Hi-Gloss Polyurethane Paint, Rockguard			
DIMENSIONS					
Total Length (ft)	29.2		31.5		
Fixed Deck Length (ft)	20		20		
Tilt Deck or Tail Length (ft)	2.5		2.5		
Deck Width (in) - (inside fender to fender)	102		102		
Deck Height (in)	33	33		33	
INCLUDED EQUIPMENT					
Hitch Type	PowerPin™ Pintle		Gooseneck		
Jackleg Wind Type - Top or Side	Side			Side	
Jackleg Speeds	Single	Dual	Single	Dual	
Jackleg Lift Capacity (lb)	20000		20000		
Steel Fender Panels	•				
Wheel Size		16" rim - 8 stud - 6.5" circle		16" rim - 8 stud - 6.5" circle	
Tire Size	ST235/80R	ST235/80R16 LRE		ST235/80R16 LRE	
EASY TO OPERATE - SAFETY & CONVENIENCE FEATURES					
Spring Assist Flip Up Style Ramps - 2' x 6' (Flat) or 2' x 8' (Ramp) Dual Chains c/w hook latches - 36"	•		•		
Arctic Cold Weather Wiring					
Breakaway Switch (Includes LED test lights, battery & charger)			•		
Integral Footholds (with handholds on Gooseneck models)					
Rear Stabilizer Jacks	•	•			
Tier 1 LED Lighting System	•				
Premium Radial 10 ply Tires (Speed Rated to 120 kph)	•				
Forward Self-Adjusting Brakes	•				
Super Lube Easy Grease Axle Bearings		•		•	
Deck Stop	0	•			
Heavy Duty Toolbox				•	
Open Top or Mesh Tray	•		•		
Black (Silver for Dual) Steel Wheels	•		•		
Aluminum Spoke Wheels	0	•	0	•	
ADDITIONAL FEATURES					
Tie Down Kit - 4x5000 lb WLL Chains c/w hooks, 4 ratchet	0		0		
Mud Flaps	0	•	0	•	
Chain Rack (Gooseneck Models)	0	•	0	•	
Spare Tire Carrier	0	•	0	•	
Spare Tire	0	•	0	•	