



STRAIGHT BODY AND MAX BODY™
UGD1116 / UPD1116

DUMP TRAILERS



INDUSTRY BEST WARRANTY

2 YEAR WARRANTY

Unmatched Two-Year Bumper-to-Bumper Warranty on all components. Five-Year Structural Warranty. *Ask us for details.*

FLEXIBLE FINANCING

Custom financing solutions available to best suit your business. *Ask us for details.*

HITCH TYPE
**PowerPin™
Pintle,
Gooseneck**

GVWR
22,000 lb

BODY LENGTH
16 Feet

RATED PAYLOAD
**15,100 –
16,200 lb**

Get Your Fill, Every Time.

Brandt Work Ready™ dump trailers are purpose-built to stand up against the toughest conditions, every day. Whether you're hauling equipment to the jobsite or aggregate when you're there, these trailers work as hard as you do and take all the punishment you can dish out.

① Easier to Own

Brandt trailers are backed by the best support in the business to make ownership stress-free:

- Flexible purchasing options include rentals, rental purchasing, leasing, and conventional financing.
- Coast-to-coast 56-branch support network ensures parts and service are easily accessible, anywhere in Canada.
- Reliable design and long-lasting components reduce total cost of ownership.

② Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Two-way gate, barn door, or two-way hydraulic gate ramp options are available, allowing the trailer to be optimized for the task at hand.
- Three-way hydraulic hoist cylinder delivers the muscle required to dump heavy loads with ease.

③ Safer

Safety is critical on the jobsite, so these models are designed with key features to maximize operator protection:

- Rugged slipper spring suspension system is optimized to safely distribute weight between axles when carrying heavy loads on uneven ground.
- Safety prop-rod secures the box in the raised position, maximizing operator safety while performing maintenance on the trailer.
- Forward self-adjusting brakes keep the brakes at their peak performance for longer while eliminating the need for manual adjustments.

Powerful Value. **Delivered.**

Brandt

DUMP TRAILER SPECIFICATIONS

INDUSTRIAL TRAILER QUICK REFERENCE CHART				UPD1116 Tridem Straight Body			UPD1116 Tridem Max Body™			UGD1116 Tridem Straight Body			UGD1116 Tridem Max Body™	
Base Unit Key Specifications				PERF	PREM	PLAT	PERF	PREM		PERF	PREM	PLAT	PERF	PREM
RELIABILITY - RATED CAPACITY														
GVWR (lb)	22000			22000			22000			22000			22000	
Rated Payload (lb)	16100	15900	15800	16200	15800		15300	15100	15100	15300		15100	15300	15100
Tongue Weight (lb)	2200			2200			4400			4400			4400	
Axle Type (Bolt On)	Equalized Leaf Spring			Equalized Leaf Spring			Equalized Leaf Spring			Equalized Leaf Spring			Equalized Leaf Spring	
Axle Rating (lb)	3 x 7000			3 x 7000			3 x 7000			3 x 7000			3 x 7000	
DURABILITY - STRUCTURE														
HSS Mainframe Size (in)	8			8			8+3			8+3			8+3	
Decking/Floor Material	10 Gauge Steel			10 Gauge Steel			10 Gauge Steel			10 Gauge Steel			10 Gauge Steel	
Paint Finish	Polyurethane Primer + Hi-Gloss Polyurethane Paint						Polyurethane Primer + Hi-Gloss Polyurethane Paint							
Side Height and Material (If applicable)	18.5" - 10 Gauge Steel			21.75" - 10 Gauge Steel			18.5" - 10 Gauge Steel			21.75" - 10 Gauge Steel				
DIMENSIONS														
Total Length (ft)	22.25	22.81	22.25	22.25	22.81		25.31	25.91	25.38	25.31		25.91	25.31	25.91
Fixed Body Length (ft)	16			16			16			16			16	
Deck Width (in) - (inside fender to fender)	82			82/97.2			82			82/97.2			82/97.2	
Deck/Floor Height (in) (Unloaded/Loaded)	25.3/23			25.3/23			25.3/23			25.3/23			25.3/23	
INCLUDED EQUIPMENT														
Hitch Type	PowerPin™ Pintle			PowerPin™ Pintle			Gooseneck			Gooseneck			Gooseneck	
Jackleg Wind Type - Top or Side	Side			Side			Side			Side			Side	
Jackleg Lift Capacity (lb)	10000			10000			10000			10000			10000	
Gate Type	2-way	Combo	2-way power	2-way	Combo		2-way	Combo	2-way power	2-way		Combo	2-way	Combo
Main Hydraulic Damping or Dump Hoist Cylinder(s)	6" - 3200 psi -20 Stroke						6" - 3200 psi - 20" Stroke							
HPU Type (P=Power Up/Down, G=Gravity Down)	P/G	P/G	P	P/G			P/G	P/G	P	P/G			P/G	
Wheel Size	16" rim - 8 stud - 6.5" circle			16" rim - 8 stud - 6.5" circle			16" rim - 8 stud - 6.5" circle			16" rim - 8 stud - 6.5" circle			16" rim - 8 stud - 6.5" circle	
Tire Size	ST235/80R16 LRE			ST235/80R16 LRE			ST235/80R16 LRE			ST235/80R16 LRE			ST235/80R16 LRE	
EASY TO OPERATE - SAFETY & CONVENIENCE FEATURES														
Dual Chains c/w hook latches - 36"	●			●			●			●			●	
Four 4"v D-Rings	●			●			●			●			●	
Arctic Cold Weather Wiring	●			●			●			●			●	
Breakaway Switch (Includes LED test lights, battery & charger)	●			●			●			●			●	
Tier 1 LED Lighting System	●			●			●			●			●	
Premium Radial 10 ply Tires (Speed Rated to 120 kph)	●			●			●			●			●	
Forward Self-Adjusting Brakes	●			●			●			●			●	
Super Lube Easy Grease Axle Bearings	●			●			●			●			●	
Heavy Duty Toolbox	●			●			●			●			●	
Safety Prop Rod	●			●			●			●			●	
110V Shore Charging Plug In	●			●			●			●			●	
Bucket Shelf - Max Body™ Models				●						●			●	
Black Steel Wheels	●	●		●			●	●		●	●		●	
Aluminum Spoke Wheels	○	○	●	○			○	○	●	○	○	●	○	
Steel Tread Plate Fenders (Bolt On)	●			●			●			●			●	
ADDITIONAL FEATURES														
Michels Premium Mesh Tarp	●			●			●			●			●	
Side Board Brackets	●			○			●			○			○	
Mud Flaps	○	○	●	○			○	○	●	○	○	●	○	
Spare Tire Carrier	○	○	●	○			○	○	●	○	○	●	○	
Spare Tire	○	○	●	○			○	○	●	○	○	●	○	
Additional Premium Rock guard on Front Facing Surfaces		●	●		●			●	●		●	●		●
HD Charge Kit	○			○			○			○			○	
Hydraulic Jack	○			○			○			○			○	
Wireless Pump Remotes	○			○			○			○			○	

● Included at no extra cost ○ Option available | AVAILABLE ACCESSORIES: Bumper Pull/Pintle/Gooseneck Locks, Wheel Locks, JDLINK™ (fleet tracking), 12V High Amp Charging Cable and Wireless Remote