

UPR1628

16-TON TRAILERS



Road Warrior.

The Brandt Work Ready[™] 16-ton ramp deck trailer delivers superior capacity to get your equipment where it's going, every single day. This rugged model works as hard as you do, while taking all the punishment you can dish out.

1 Easier to Own

Brandt trailers are backed by the best support in the business to make ownership stress-free:

- Flexible purchasing options include rentals, rental purchasing, leasing, and conventional financing.
- Coast-to-coast 56-branch support network ensures parts and service are easily accessible, anywhere in Canada.
- Reliable design and long-lasting components reduce total cost of ownership.

2 Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Full-width ramps accommodate any kind of equipment without hassle, ensuring superior versatility.
- Dual Two-speed 10,000 lb. jack is included as standard equipment to make coupling an uncoupling trailer effortless.

Safer

Safety is critical on the jobsite, so these models are designed with key features to maximize operator protection:

- Optional undercarriage toolbox, lower side step, and hydraulic ramps allow operators to work safely.
- Dependable 15,000 lb. axles on platinum configurations ensure positive hitch weight distribution and overall stability when hauling concentrated heavy payloads.
- Premium fir decking provides better traction for the operator in wet and frozen conditions.



16-TON TRAILER SPECIFICATIONS

INDUSTRIAL TRAILER QUICK REFERENCE CHART	UPR1628 Tandem Dualies	
Base Unit Key Specifications	PERFORMANCE	PLATINUM
RELIABILITY - RATED CAPACITY		
GVWR (lb)	32000	
Rated Payload (lb)	23500	23400
Tongue Weight (lb)	4000	4000
Axle Type (Bolt On)	Equalized Leaf Spring - Dual	
Axle Rating (lb)	3 x 10000	2 x 15000
DURABILITY - STRUCTURE		
HSS Mainframe Size (in)	W14X22, 50W	
Decking Material	Premium Fir	
Paint Finish	Polyurethane Primer + Hi-Gloss Polyurethane Paint	
DIMENSIONS	1 organization in the 1 th alough of discharge faint	
Total Length (ft)	39.6	
Fixed Deck Length (ft)	28	
Tilt Deck or Tail Length (ft)	5.8	
Deck Width (in) - (inside fender to fender)	102	
Deck Height (in)	38.3	
INCLUDED EQUIPMENT	30	
Hitch Type	PowerPin™ Pintle	
Jackleg Wind Type - Top or Side	Side	Hydraulic
Jackleg Speeds	Dual	Single
Jackleg Lift Capacity (lb)	10000	10000
Wheel Size	Dual Rim 8 - stud - 6.5" circle	Dual Rim 8 - stud - 275mm circle
Tire Size	ST235/80R16 LRE	ST215/75R17.5 LRH
Corded Pump Remote	31233/60N10 ENL	31213/73N17.3 ENTI
EASY TO OPERATE - SAFETY & CONVENIENCE FEAT	FLIDES	•
Spring Assist Full Width Beavertail Ramp - 4' x 6'	ONES	
Hydraulic Full Width Beavertail Ramp - 8' x 6'		•
Dual Chains c/w hook latches - 36"		
Arctic Cold Weather Wiring		
Breakaway Switch (Includes LED test lights, battery & charger)		
Underbody Toolbox		•
Step Ladder	•	•
Tier 1 LED Lighting System	-)
Forward Self-Adjusting Brakes		
Super Lube Easy Grease Axle Bearings		
Deck Stop		
Heavy Duty Toolbox	0	•
110V Shore Charging Plug In		•
Black (Silver for Dual) Steel Wheels	•	•
ADDITIONAL FEATURES		
Tie Down Kit - 4x5000 lb WLL Chains c/w hooks, 4 ratchet)
Mud Flaps		
Spare Tire Carrier and Wheel	0	•
Bumper Pull/Pintle/Gooseneck Locks)
Wheel Locks		
JD Link (Fleet Tracking)		
HD Charge Kit		0
Hydraulic Jack		0
Wireless Pump Remotes		0
		•