



MASSEY FERGUSON

SCAN THE QR CODE

TO FIND YOUR LOCAL DEALER AND LEARN
MORE ABOUT OUR OFFERINGS



©2024 AGCO Corporation. Massey Ferguson is a worldwide brand of AGCO Corporation. AGCO and Massey Ferguson are trademarks of AGCO. All rights reserved. | MF24S001BSv03



MASSEY FERGUSON

BORN TO **FARM**



MF 3 SERIES // 75-115 HP

GROUND EFFECT // SPECIALTY // VINEYARD



MF 3 Ground Effect (3GE) // 75-105 HP*

- ▶ Available in platform version only
- ▶ Ideal for work under trees, polytunnels or canopied vineyards
- ▶ Foldable ROPS makes it easy for operators to access low clearance areas



MF 3 Specialty (3SP) // 75-115 HP

- ▶ Designed for more open vineyards
- ▶ More spacious cab compared to our vineyard version
- ▶ Wide range of HP options making it suitable for many operations



MF 3 Vineyard (3VI) // 95 HP

- ▶ Ideal for use in traditional narrow vineyards
- ▶ Available in cab version only
- ▶ Cab measures a little over 3-feet wide

The Massey Ferguson® 3 Series Specialty tractor is the straightforward and dependable solution for specialty farmers who need to tackle a wide range of tasks. This powerful, fuel-efficient tractor features the new MF saber styling and is available in three versions with numerous cab, platform and horsepower options, so you can choose the version that works best for your operation.

Standard Features // All Models

- » Open Center Hydraulic System
- » PTO Type — 540/540E
- » Steering flow of 7.9 gpm
- » Implement Flow — 17.6 gpm
- » Stage V compliant
- » Horizontal exhaust & low hood height providing the best visibility and maneuverability

Standard Features // 75 HP

- » 3.4 L, 4-cylinder diesel engine
- » 19.8 gallon fuel tank
- » Good value for the market while having the necessary features to get the job done

Standard Features // >75 HP

- » 3.6 L, 4-cylinder diesel engine
- » 19.8 gallon fuel tank with optional 26.1 gallon on SP models
- » Best-in class cab environment from the semi-flat front floor, additional headroom and enhanced control layout

MODEL	Rated Engine (HP)	Operator Environment	Transmission	3-Point Lift Capacity 24" BEHIND (LBS)	Machine Width External Fender (IN)	Machine Height With Tires (IN)	Rear Spool Valves
MF 3SP.75	75	Cab	24F/24R synchro shuttle Optional — 24F/12R — power shuttle with speed shift	5511.5	51.2"	94.6"	2 rear spool valves with an optional third
MF 3GE.75	75	Platform		4409.2	45.3"	100.9"	
MF 3SP.95	95	Cab	30F/30R Synchro Shuttle Optional — 30F/15R power shuttle with speed shift	5511.5	51.2"	96.8"	
MF 3VI.95	95	Cab		5511.5	39.4"	96.8"	
MF 3GE.95	95	Platform	24F/24R synchro shuttle Optional — 24F/12R — power shuttle with speed shift	4409.2	45.3"	105.3"	
MF 3GE.105	105	Platform		4409.2	45.3"	105.3"	
MF 3SP.115	115	Cab	30F/30R Synchro Shuttle Optional — 30F/15R power shuttle with speed shift	5511.5	51.2"	96.8"	

*Please refer to your manual on correct operation of foldable ROPS and follow all safety instructions.