



MADE TO WORK. BUILT TO LAST.

SPECIFICATIONS:

F1-20						
WORKING WIDTH	WEIGHT	DRUM DIAMETER	TRANSPORT CLEARANCE	TRANSPORT WIDTH	TRANSPORT LENGTH	TIRES
20' (6.1 M)	7,600 lbs (3,447 kg)	42" (107 cm)	16" (41 cm)	8' (2.4 M)	27' (8.2 M)	12.5 L X 15-12 PLY

FIXED-HITCH						
MODEL	WEIGHT	DRUM DIAMETER	WING CONFIGURATION	TRANSPORT WIDTH	TRANSPORT LENGTH	TIRES
FH-12	5,000 lbs (2,268 kg)	42" (107 cm)	12' (3.8 m)	13' (4.1 m)	13' 11" (4.2 m)	11 L x 15 - 8 PLY
FH-14	5,500 lbs (2,485 kg)	42" (107 cm)	14' (4.3 m)	15' (4.6 m)	13' 11" (4.2 m)	11 L x 15 - 8 PLY
FH-16	6,000 lbs (2,722 kg)	42" (107 cm)	16' (4.9 m)	17' (5.2 m)	13' 11" (4.2 m)	11 L x 15 - 8 PLY
FH-18	6,500 lbs (2,948 kg)	42" (107 cm)	18' (5.5 m)	19' (5.8 m)	13' 11" (4.2 m)	11 L x 15 - 8 PLY
FH-20	7,000 lbs (3,175 kg)	42" (107 cm)	20' (6.1 m)	21' (6.4 m)	13' 11" (4.2 m)	12.5 L x 15-12 PLY



We are continuously improving our products. Design, specifications, and material are subject to change without notice.

For more information on the 1-section Rollers or other land improvement equipment, visit your local Rite Way equipment dealer or www.RiteWayMfg.com. Toll free: 1-800-352-8822

