



MADE TO WORK. BUILT TO LAST.

Short or long, and designed to shape to your field, the Rite Way Land Rollers prepare your land for optimum performance. Customize your equipment to be as aggressive as you need with a field-proven design and a range of sizes and working width options.

SPECIFICATIONS:

F-3						
MODEL	WORKING WIDTH	WING CONFIGURATION	TRANSPORT LENGTH	TRANSPORT WIDTH	WEIGHT 1/2" DRUM	WEIGHT 5/8" DRUM
F3-32	32' (9.8 m)	10'-12'-10' (3.1 m-3.6 m-3.1 m)	38' (11.6 m)	14' (4.3 m)	17,640 lbs (8,100 kg)	19,560 lbs
F3-36	36' (11.0 m)	12'-12'-12' (3.6 m-3.6 m-3.6 m)	40' (12.2 m)	14' (4.3 m)	19,000 lbs (8,618 kg)	21,160 lbs
F3-42	42' (12.8 m)	15'-12'-15' (4.5 m-3.6 m-4.5 m)	45' (13.7 m)	14' (4.3 m)	21,220 lbs (9,625 kg)	23,740 lbs
F3-46	46' (14.1 m)	17'-12'-17' (5.2 m-3.6 m-5.2 m)	47' (14.3 m)	14' (4.3 m)	22,910 lbs (10,391 kg)	25,670 lbs
F3-52	52' (15.8 m)	20'-12'-20' (6.1 m-3.6 m-6.1 m)	50' (15.2 m)	14' (4.3 m)	24,400 lbs (11,067 kg)	27,520 lbs
F3-40 NT	40' (12.2 m)	15'-10'-15' (4.5 m-3.1 m-4.5 m)	45' (13.7 m)	12' (3.7 m)	20,600 lbs (9,344 kg)	23,000 lbs
F3-50 NT	50' (15.2 m)	20'-10'-20' (6.1 m-3.6 m-6.1 m)	50' (15.2 m)	12' (3.7 m)	23,100 lbs (10,478 kg)	26,100 lbs

F-5						
MODEL	WORKING WIDTH	WING CONFIGURATION	TRANSPORT LENGTH	TRANSPORT WIDTH	WEIGHT 1/2" DRUM	WEIGHT 5/8" DRUM
F5-46	46' (14 m)	8'-8'-12'-8'-8' (2.4 m-2.4 m-3.6 m-2.4 m-2.4 m)	47' 4" (14.4 m)	14' (4.3 m)	23,000 lbs (10,432 kg)	25,640 lbs
F5-50	50' (14.4 m)	10'-8'-12'-8'-10' (3.1 m-2.4 m-3.6 m-2.4 m-3.1 m)	49' 4" (15.0 m)	14' (4.3 m)	24,800 lbs (11,249 kg)	27,680 lbs
F5-54	54' (16.4 m)	10'-10'-12'-10'-10' (3.1 m-3.1 m-3.6 m-3.1 m-3.1 m)	51' 4" (15.6 m)	14' (4.3 m)	26,490 lbs (12,016 kg)	29,610 lbs
F5-58	58' (17.7 m)	12'-10'-12'-10'-12' (3.6 m-3.1 m-3.6 m-3.1 m-3.6 m)	53' 4" (16.2 m)	14' (4.3 m)	28,478 lbs (12,917 kg)	31,838 lbs
F5-62	62' (18.9 m)	12'-12'-12'-12'-12' (3.6 m-3.6 m-3.6 m-3.6 m-3.6 m)	55' 4" (16.9 m)	14' (4.3 m)	30,250 lbs (13,721 kg)	33,850 lbs
F5-68	68' 4" (20.8 m)	12'-15'-12'-15'-12' (3.6 m-4.5 m-3.6 m-4.5 m-3.6 m)	61' 6" (18.7 m)	14' (4.3 m)	32,620 lbs (14,796 kg)	36,580 lbs
F5-74	74' (22.5 m)	15'-15'-12'-15'-15' (4.5 m-4.5 m-3.6 m-4.5 m-4.5 m)	64' 6" (19.7 m)	14' (4.3 m)	35,520 lbs (16,112 kg)	—
F5-78	78' (23.7 m)	17'-15'-12'-15'-17' (5.2 m-4.5 m-3.6 m-4.5 m-5.2 m)	66' 6" (20.3 m)	14' (4.3 m)	37,440 lbs (16,982 kg)	—
F5-84	84' (25.6 m)	20'-15'-12'-15'-20' (6.1 m-4.5 m-3.6 m-4.5 m-6.1 m)	69' 6" (21.2 m)	14' (4.3 m)	40,320 lbs (18,289 kg)	—

F-7					
MODEL	WORKING WIDTH	WING CONFIGURATION	TRANSPORT LENGTH	TRANSPORT WIDTH	WEIGHT 1/2" DRUM
F7-65	65' (19.8 m)	8'-8'-8'-12'-8'-8'-8' (2.4 m-2.4 m-2.4 m-3.6 m-2.4 m-2.4 m-2.4 m)	59' 8" (18.2 m)	14' (4.3 m)	32,500 lbs (32,500 kg)
F7-69	69' (21.0 m)	10'-8'-8'-12'-8'-8'-10' (3.1 m-2.4 m-2.4 m-3.6 m-2.4 m-2.4 m-3.1 m)	61' 8" (18.2 m)	14' (4.3 m)	33,740 lbs (15,304 kg)
F7-73	73' (22.3 m)	10'-10'-8'-12'-8'-10'-10' (3.1 m-3.1 m-2.4 m-3.6 m-2.4 m-3.1 m-3.1 m)	62' 6" (19.0 m)	14' (4.3 m)	35,040 lbs (15,894 kg)
F7-77	77' (23.5 m)	12'-10'-8'-12'-8'-10'-12' (3.6 m-3.1 m-2.4 m-3.6 m-2.4 m-3.1 m-3.6 m)	65' 8" (20.0 m)	14' (4.3 m)	36,960 lbs (16,765 kg)
F7-81	81' (26.7 m)	12'-10'-10'-12'-10'-10'-12' (3.6 m-3.1 m-3.1 m-3.6 m-3.1 m-3.1 m-3.6 m)	67' 8" (20.6 m)	14' (4.3 m)	38,718 lbs (17,562 kg)
F7-85	85' (25.9 m)	12'-12'-10'-12'-10'-12'-12' (3.6 m-3.6 m-3.1 m-3.6 m-3.1 m-3.6 m-3.6 m)	69' 8" (21.2 m)	14' (4.3 m)	39,950 lbs (18,121 kg)
F7-89	89' (27.1 m)	12'-12'-12'-12'-12'-12'-12' (3.6 m-3.6 m-3.6 m-3.6 m-3.6 m-3.6 m-3.6 m)	71' 8" (21.8 m)	14' (4.3 m)	41,190 lbs (18,683 kg)

TIRES		
MODEL	MAIN FRAME	WING AXLE
F3-32 to F3-42	11L x 15-12 ply	11L x 15-12 ply
F3-46 to F3-52	12.5L x 15-12 ply	12.5L x 15-12 ply
F3-40 NT	11L x 15-12 ply	11L x 15-12 ply
F3-50 NT	12.5L x 15-12 ply	12.5L x 15-12 ply
F5-46 to F5-58	12.5L x 15-12 ply	12.5L x 15-12 ply
F5-62 to F5-84	380/55R16.5	12.5L x 15-12 ply
F7	380/55R16.5	12.5L x 15-12 ply
**TRUCK TIRES AVAILABLE UPON REQUEST		

We are continuously improving our products. Design, specifications, and material are subject to change without notice.

For more information on the Land Roller Series or other land improvement equipment, visit your local Rite Way equipment dealer, or visit www.RiteWayMfg.com

Toll free: 1-800-352-8822  /RiteWayMfg  @RiteWayMfgCo

