

Rear Blades

SERIES >>																		
MODEL >>	3048	3060	3072	4560	4572	4584	6084	6096	8084	8096	80108	10096	100108	15596	155108	155120	155144	
Maximum hp	30	30	30	45	45	45	60	60	80	80	80	100	100	155	155	155	155	
3-point hitch	Category I			Category I			Category I & II		Category II			Category II & III		Category II & III				
Moldboard thickness	1/4"			1/4"			1/4"		1/4" Boxed reinforcement			5/16" Boxed reinforcement						
Moldboard width	48"	60"	72"	60"	72"	84"	84"	96"	84"	96"	108"	96"	108"	96"	108"	120"	144"	
Moldboard height	12 1/2"			13"			16"		18"			18"		21.25"				
Adjustment	Manual 5-position			Manual 5-position			Manual 5-position		Manual or hydraulic			Manual or hydraulic		Manual or hydraulic				
Adjustment, angle	30° left or right			40° left or right			40° left or right		30° left or right			30° left or right		30° left or right				
Adjustment, tilt	3-point hitch linkage adj.			Manual 15° blade adjustment			3-point hitch linkage adj.		Manual or hydraulic 13° blade adjustment									
Offset	N/A			N/A			N/A		Manual or hydraulic 20° left or right									
Sideshift	N/A			Up to 12" off center			N/A		N/A			N/A		N/A				
King pin	N/A			N/A			N/A		3"			3 1/2"		4"				
Cutting edge	1/4" x 3" reversible			High carbon 1/2" x 6" reversible						High carbon 1/2" x 6" reversible								
Weight, lb	130	155	180	263	283	289	405	450	939	969	989	1287	1352	1683	1710	1749	1846	
Dual gauge wheel kit	N/A			N/A			N/A		Optional			Optional		Optional				
Skid shoes	N/A			N/A			N/A		Optional			Optional		Optional				
Racket jack	N/A			N/A			N/A		Optional			Optional		Optional				