

RTX1250

RIDE-ON TRACTOR



PRODUCTIVITY PACKAGE. Cut trenches confidently and efficiently with TrenchSense™ electronic control system, Ecolde™ engine control system, Productivity Zone, and Auto Plunge. Continuously cut with a sod knife designed to minimize buildup and keep you running.



VERMEER FLEET-READY. Stay in-sync with your machine and optimize productivity by adding Vermeer telematics to this tractor.



5,000 LB REEL CARRIER ATTACHMENT OPTION. On the tractor equipped with a plow, add a reel carrier attachment capable of carrying up to 5,000 lbs of product.



OPERATOR COMFORT. Work comfortably with a quiet ride, convenient single-side controls and an isolated, cushioned operator's platform. Go year-round with an optional climate-controlled cab.



POWER FOR THE JOB. Take on difficult ground conditions with the efficient power of a 127-hp (95- kW) Deutz TCD3.6L diesel engine.

RTX1250 RIDE-ON TRACTOR

GENERAL DIMENSIONS AND WEIGHTS

Weight (basic tractor, rubber tires): 11,580 lb (5,253 kg)

Weight (basic tractor, tracks): 16,380 lb (7,429.8 kg)

Weight (cab, rubber tires): 12,630 lb (5,729 kg)

Weight (cab, tracks): 17,430 lb (7,865.3 kg)

Length (basic tractor, rubber tires): 139.2 in (354.3 cm)

Length (basic tractor, tracks): 149 in (378.5 m)

Width (basic tractor, rubber tires): 86 in (21.8 cm)

Width (basic tractor, tracks): 92.5 in (23.5 cm)

Width (cab, rubber tires): 87.5 in (22.3 cm)

Height (basic tractor, rubber tires): 115 in (292.1 cm)

Height (basic tractor, tracks): 115 in (292.1 cm)

Height (cab, rubber tires): 115 in (292.1 cm)

Height (cab, tracks): 115 in (292.1 cm)

Roll Over Protection Structure (Closed Cab): 40,000 lb (18,143.7 kg)

Roll Over Protection Structure (Open Cab): 40,000 lb (18,143.7 kg)

ENGINE OPTION ONE

Make and model: Deutz TCD3.6L

Gross horsepower: 127 hp (94.7 kW)

Max torque: 369 lb-ft (500.3 Nm)

Cooling method: Liquid

Fuel type: Ultra-low sulfur diesel

Emissions rating: Tier 4 Final (Stage V)

ENGINE OPTION TWO

Make and model: Deutz TCD3.6L

Gross horsepower: 127 hp (94.7 kW)

Max torque: 369 lb-ft (500.3 Nm)

Cooling method: Liquid

Emissions rating: Tier 3 (Stage IIIA)

FEATURES

Front axle type: Steerable planetary with hydraulic 100% differential lock

Rear axle type: Steerable planetary with hydraulic 100% differential lock

Axle load rating (static, per axle): 49,458 lb (22,434 kg)

Outside turning diameter (rubber tires, front steer only): 40 ft (12 m)

Outside turning diameter (rubber tires, front and rear steer): 23 ft (6.9 m)

Service brake type: Hydrostatic

Parking brake type: Spring applied hydraulic release

CAPACITIES

Fuel tank: 44 gal (166.8 L)

Hydraulic tank: 31.6 gal (119.8 L)

Coolant: 4.9 gal (18.6 L)

ATTACHMENT OPTIONS

Front options:

Backhoe

Backfill blade

Reel carrier

Back options:

Vibratory plow

Rockwheel

Sliding offset rockwheel

Sliding offset trencher

Trencher

NOTES:

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More and TrenchSense are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Deutz is a trademark of Klockner-Humboldt-Deutz Corporation. © 2023 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

Vermeer



EQUIPPED TO
DO MORE.