



BS62-4Ab/28

4-stroke Rammers

Outstanding work performance and long service life

Wacker Neuson's 4 stroke rammers characterized by excellent work performance. The long shoe stroke, the high ramming frequency, high impact energy and fast travel speed ensure first-class work results. Well thought-out functions make the use of the 4 stroke rammers even more operator-friendly, extend their service life, and minimize maintenance.

Highlights

- Large stroke, high impact force
- Just one lever for starting, idling and stopping
- Efficient air filter
- Ergonomic guide handle
- Low oil warning indicator
- Large stroke, high impact force
- Efficient air filter
- Ergonomic guide handle

Technical Data

■ Mechanical - Output Details

| | |
|-----------------|-------------------------|
| Number of blows | 689.0 1/min |
| Area capacity | 202.0 m ² /h |
| Forward running | 12.0 m/min |
| Power of impact | 17.0 kN |

■ Mechanical Details

| | |
|---------------------|----------|
| Length | 662.0 mm |
| Length Ramming Shoe | 340.0 mm |
| Width | 347.0 mm |
| Width Ramming Shoe | 280.0 mm |
| Height | 920.0 mm |
| Weight | 63.30 kg |
| Operating weight | 64.0 kg |

stroke at tamper 68.0 mm

■ Environment Data

| | |
|-------------------------------|-----------------------|
| Operating temperature range | -10 - 40 °C |
| Sound power LWA, guaranteed | 108.0 dB(A) |
| Sound power LWA (Standard) | EN 500-4 |
| HAV summation (average value) | 10.0 m/s ² |
| HAV summation (Standard) | EN 500-4 |

■ Electrical System

| | |
|--------------------|----------------|
| Display Equipment | Beacon |
| Operating elements | Pushbutton OFF |

■ Operating Fluids

| | |
|-------------------|------------|
| Oil specification | SAE 10W-40 |
| Oil volume | 0.700 l |