



E3000

Hydronic Heater

dual reeled hydronic heater for the toughest jobs.

Engineered for reliable performance and trouble-free starts for up to 140 hours of run time, the E3000 will provide maximum flow and ensure consistent heat delivery for thawing and curing applications. The E3000 thaws or cures up to 6,000 sq. ft. With accessories this heater will cure up to 18,000 sq. ft. or provide 535,000 cu. ft. of dry heat at 83% efficiency, the highest in the industry.

Highlights

- Powerful positive displacement pumps
- Dual hose reels

Technical Data

loolinioal Bata			
Electrical - Output Details		Engine	
Nominal current	20.00 A	Cooling	Water-cooling
Nominal voltage	120.0 V	Engine type	Diesel engine
Mechanical Details		Cylinder	3.0
Length	4,600.0 mm	Cylinder capacity	1,028.0 cm3
Gross Axle Weight Rating	2,304.0 kg	Operating Engine speed	1,800.0 1/min
Width	2,300.0 mm	Engine Manufacturer	Kohler
Height	2,400.0 mm	Environment Data	
Operating weight	4,076.0 kg	Operating temperature range	38 - 82 °C
Dry Weight	3,406.0 kg	Electrical System	
Gross vehicular weight	4,076.0 kg	Temperature monitor	digital
Lift Bail - quantity	1.0	Operating Fluids	
Length hose	914.0 m	Oil volume	3.800 l
Generator		Fuel specification	Winter Blend Diesel No. 2
Insulation class	Н	Run Time (75 % Prime Load)	108.0 hrs
Output current 1~	30.0 A	Fuel Tank capacity	871.0 l
Output voltage	120.0 V	Utilizable tank capacity	840.0 l
Output frequency	60.0 Hz	Fuel Consumption no genset	10.4 L/hr
Nominal power	6.0 KW	Fuel Consumption with genset	12.7 L/hr
Voltage Regulation - Steady State	6.0 %	Run Time (100 %)	81.0 hrs
Generator Manufacturer	Mecc Alte	Chassis	
Generator specification	Brushless with capacitor	Brake	Electric brake
Genset	yes	Tongue Weight, min.	384.0 kg
		Tongue Weight, max.	521.0 kg

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.

Shipping and Storage

Shipping weight with Trailer

4,076.0 kg

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.