



PG2A

Dewatering Pump

Clear water from your job site or swimming pool quickly with Wacker Neuson dewatering pump.

With its self-priming centrifugal pumping action and overall compact size, the pump is ideal for the contractor with the need for temporary water removal.

Highlights

- Pump out vanes on back of impeller.
- Cast iron impeller and volute for long life and minimal service
- Carbon ceramic mechanical seal.

Technical Data

Mechanical - Output Details

| | |
|----------------------|-------------|
| Flow rate max. | 639.0 l/min |
| Solid diameter max. | 6.5 mm |
| Suction head max. | 7.6 m |
| Delivery height max. | 27.0 m |

Mechanical Details

| | |
|------------------------------|----------|
| Length | 480.0 mm |
| Width | 375.0 mm |
| Height | 395.0 mm |
| Operating weight | 25.0 kg |
| Intake-/Pressure socket-dia. | 50.0 mm |

Engine

| | |
|---------|-------------|
| Cooling | air cooling |
|---------|-------------|

| | |
|----------------------------|-----------------------|
| Engine type | Gasoline engine |
| Engine operating mode | four-stroke |
| Cylinder | 1.0 |
| Cylinder capacity | 118.0 cm ³ |
| Kraftstofftyp | Gasoline |
| Fuel consumption | 1.3 L/hr |
| Tank capacity | 2.5 l |
| Oil filling max. | 0.6 l |
| Power rating max. | 2.6 KW |
| Engine speed (Power max.) | 3,600.0 1/min |
| Standard (Operating power) | SAE J1349 |
| Engine Manufacturer | Honda |
| Running time at 100% | 1.9 hrs |