



## PS3 1500

### Submersible Pump

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Pump can start in low water levels when it is primed through the discharge port. No matter how large or small the job. Wacker Neuson submersible pumps offer the versatility and durability contractors need for light dewatering. Suitable for most outlets, these pumps offer big pump features for small pump investment.

### Highlights

- Built-in thermal protection prevents motor damage
- Lightweight, compact design
- Durable mechanical seals
- Heavy-duty strain relief power cord
- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

### Technical Data

#### ■ Mechanical - Output Details

Flow rate max.	420.0 l/min
Solid diameter max.	8.5 mm
Delivery height max.	21.0 m

#### ■ Mechanical Details

Length	240.0 mm
Width	240.0 mm
Height	570.0 mm
Operating weight	28.8 kg
Intake-/Pressure socket-dia.	80.0 mm

#### ■ Motor

Nominal power	1.50 KW
Nominal current	23.0 A
Nominal voltage	110.0 V

Nominal frequency	60.0 Hz
Nominal speed	3,440.0 1/min

#### ■ Environment Data

Temp. limit borrowed liquid	40.0 °C
-----------------------------	---------

#### ■ Electrical System

Length Cable	10.0 m
Cable cross-section	3.5 mm <sup>2</sup>
Cable definition	PVC Sheath

#### ■ Shipping and Storage

Length for shipping	345.0 mm
Width for shipping	330.0 mm
Height for shipping	710.0 mm
Shipping weight	35.0 kg