



## PST3 750

### Submersible Pump

Durable, lightweight and perfect for any job

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

## Highlights

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

## Technical Data

### ■ Mechanical - Output Details

Flow rate max.	240.0 l/min
Solid diameter max.	6.0 mm
Delivery height max.	12.0 m

### ■ Mechanical Details

Length	317.0 mm
Width	185.0 mm
Height	388.0 mm
Operating weight	19.0 kg
Intake-/Pressure socket-dia.	80.0 mm

### ■ Motor

Nominal power	0.75 KW
Nominal current	10.0 A
Nominal voltage	110.0 V

Nominal frequency	60.0 Hz
Nominal speed	3,408.0 1/min

### ■ Environment Data

Temp. limit borrowed liquid	40.0 °C
-----------------------------	---------

### ■ Electrical System

Length Cable	10.0 m
Cable cross-section	2.0 mm <sup>2</sup>
Cable definition	PVC Sheath

### ■ Shipping and Storage

Length for shipping	483.0 mm
Width for shipping	330.0 mm
Height for shipping	260.0 mm
Shipping weight	21.9 kg