

# UFORCE U10 PRO HIGHLAND 2025

 Bordeaux Red  Nebula Black  TrueTimber Camo



**The most equipped vehicles  
on the market**  
More than \$15,150 in add-ons!

## Standard features and benefits

Rims  
**\$1,200 value**

Rear windshield  
**\$850 value**

Heater / air conditioning  
**3,500 value**

Trailer hitch  
**\$100 value**

Roof  
**\$500 value**

4,500 lbs winch  
(complete assembly)  
**\$1,000 value**

Tilting front windshield  
and wiper  
**\$2,000 value**

Audio system and speakers  
**\$1,000 value**

5-year CFMOTO warranty

Doors with  
electrical windows  
**\$4,000 value**

Safety and convenience  
package

Including:

- Side mirrors
- Retaining bars for passenger
- 12 V outlet
- Turn signals
- Horn

**\$1,000 value**

**BEST**  
**5**  
**YEAR**  
LIMITED WARRANTY

5 Year limited warranty:  
1 year complete with no mileage  
restriction + 48 months balance  
powertrain only or 5,000 km



Electric Power  
Steering



12 V outlet



CV-Tech IBC  
clutch system

## Specifications

### Engine

Type: 3 cylinder, liquid-cooled,  
DOHC, 12-valves, 4-strokes

Displacement: 998 cc

Bore & Stroke:  
80 x 66.2 mm (3.15 x 2.61 in)

Compression: 11.0: 1

Engine management:  
Fuel injected engine

Cooling system: Liquid

Starting: Electric

Battery: 30 Ah

### Size / weight

Length x Width x Height:  
2965 x 1645 x 1945 mm  
(116.7 x 64.7 x 76.5 in)

Wheelbase: 2060 mm (81.1 in)

Ground clearance: 330 mm (12.9 in)

Minimum turning radius:  
4250 mm (167.3 in)

Fuel tank capacity: 45 L (11.8 gal)

Curb weight: 970 kg (2138.5 lbs)

Payload capacity: 727 kg (1602 lbs)

Towing capacity: 1134 kg (2500 lbs)

Rear cargo box capacity:  
454 kg (1000 lbs)

### Brakes

Four wheel brake disc

### Special features

CFMOTO Ride app connectivity

### Wheels

Front wheels: Aluminum alloy (14 in)

Rear wheels: Aluminum alloy (14 in)

Front tires: AT 29 x 9-14

Rear tires: AT 29 x 11-14

### Transmission

Clutch: OmniDrive™ CVT

Gear box: P / R / N / H / L  
(parking lock shift system)

Power train: 2WD / 4WD,  
locking front differential

### Suspension and steering

Front suspension: Double A-arm  
independent, hydraulic shock  
absorber

Front travel: 280 mm (11 in)

Rear suspension: Double A-arm  
independent, hydraulic shock  
absorber

Rear travel: 260 mm (10.2 in)

Steering:  
Electric Power Steering (EPS)

### Protection plan

EASY protection plan available

**EASY** PROTECTION  
PLAN

Follow us



cfmoto.ca

\*The pictures are for illustrative purposes only and accessories shown are not included. Specifications to change without notice. Details in store.