CFORCE 400 2025







The most equipped vehicles on the market

More than \$2,800 in add-ons!

Standard features and benefits

Rims \$1,200 value

Trailer hitch \$100 value

5-year CFMOTO warranty

2,500 lbs winch (complete assembly) \$750 value

Safety and convenience package

Including:

- Side mirrors
- Trailer connector
- Anti-theft device (gear lever lock)
- USB port
- Turn signals
- Horn

\$750 value



1 year complete with no mileage restriction + 48 months balance powertrain only or 5,000 km







Specifications

Engine

Type: Single-cylinder, liquid-cooled, 4-valves, 4-strokes

Displacement: 400 cc

Bore & Stroke: 91 x 61.5 mm

(3.58 x 2.42 in)

Compression: 10.3: 1

Engine management:

Fuel injected engine

Cooling system: Liquid

Starting: Electric

Battery: 30 Ah

Size / weight

Length x Width x Height: 2046 x 1125 x 1150 mm

(80 x 44 x 45 in)

Wheelbase: 1260 mm (49.6 in)

Ground clearance: 250 mm (9.8 in)

Minimum turning radius:

2800 mm (110 in)

Fuel tank capacity: 17 L (4,5 gal)

Curb weight: 332 kg (732 lbs)

Towing capacity: 612 kg (1349 lbs)

Rack capacity (Front/Rear):

Front 30 kg (66 lbs)

Rear 60 kg (132 lbs)

Brakes

Disc brakes

Wheels

Front wheels: Aluminum alloy (12 in) Rear wheels: Aluminum alloy (12 in)

Front tires: AT 25 x 8-12 Rear tires: AT 25 x 10-12

Transmission

CV-Tech IBC clutch system:

Variable transmission

Gearbox: P/R/N/H/L (parking lock shift system)

Power train: 2WD / 4WD,

electric locking differential

Suspension and steering

Front suspension:

Double A-arm independent

Front travel: 190 mm (7.5 in)

Rear suspension:

Double A-arm independent

Rear travel: 225 mm (8.9 in)

Steering:

Electronic Power Steering (EPS)

Protection plan

EASY protection plan available











