# **UFORCE**1000 XL 2025









More than \$3,800 in add-ons!

Standard features and benefits

Rims **\$1,200 value** 

Trailer hitch \$100 value

Roof \$500 value

3,500 lbs winch (complete assembly) \$1,000 value

5-year CFMOTO warranty

Safety and convenience package

Including:

- Side mirrors
- Retaining bars for passenger
- 12 V outlet
- Turn signals
- Horn

\$1,000 value

# **Specifications**

#### **Engine**

**Type:** V-Twin cylinder, liquid cooled, SOHC, 8-valves, 4-strokes

Displacement: 963 cc

Bore & Stroke:

 $91 \times 74 \text{ mm} (3.5 \times 2.91 \text{ in})$ 

Compression: 10.6: 1

Engine management:

Fuel injected engine

Cooling system: Liquid

Starting: Electric

Battery: 30 Ah

### Size / weight

Length x Width x Height: 3745 x 1615 x 1880 mm

(147.4 x 63.5 x 74 in)

Wheelbase: 2850 mm (112.2 in)

Ground clearance: 310 mm (12 in)

Minimum turning radius:

5500 mm (216.5 in)

Fuel tank capacity: 40 L (10.6 gal)

Curb weight: 877 kg (1933 lbs)

Payload capacity: 660 kg (1455 lbs)

Towing capacity: 1134 kg (2500 lbs)

Rear cargo box capacity:

350 kg (770.9 lbs)

#### **Brakes**

Four wheel brake disc

#### Wheels

Front wheels:

Aluminum alloy  $(14 \times 7 \text{ in})$ 

Rear wheels:

Aluminum alloy (14 x 8 in)

Front tires: AT 27 x 9-14

Rear tires: AT 27 x 11-14

#### **Transmission**

CV-Tech IBC clutch system:

Variable transmission

Gear box: P/R/N/H/L

(parking lock shift system)

Power train: 2WD / 4WD,

locking front differential

# Suspension and steering

**Front suspension:** Double A-arm independent, hydraulic shock

absorber

Front travel: 230 mm (9.1 in)

**Rear suspension:** Double A-arm independent suspension, hydraulic

shock absorber

Rear travel: 220 mm (8.6 in)

Steering:

Electric Power Steering (EPS)

# Protection plan

EASY protection plan available





5 Year limited warranty: 1 year complete with no mileage restriction + 48 months balance powertrain only or 5,000 km





