UFORCE 800 XL 2025



Twilight Blue Nebula Black TrueTimber Camo

The most equipped vehicles on the market More than \$3,800 in add-ons!



12 V outlet

CVTech 4BC CV-Tech IBC

clutch system

Standard features and benefits

5-year CFMOTO warranty

Rims **\$1,200 value**

Trailer hitch **\$100 value**

Roof **\$500 value**

3,500 lbs winch (complete assembly) **\$1,000 value**

Safety and convenience package

- Including:
- Side mirrorsRetaining bars
- for passenger – 12 V outlet
- Turn signals
- Horn
- \$1,000value

Specifications

Engine

Type: V-Twin cylinder, liquid cooled, SOHC, 8-valves, 4-strokes Displacement: 800 cc Bore & Stroke: 91 x 61.5 mm (3.6 x 2.4 in) Compression: 10.8: 1 Engine management: Fuel injected engine Cooling system: Liquid Starting: Electric Battery: 28 Ah

Size / weight

Length x Width x Height: 3635 x 1525 x 2007 mm (143.1 x 60 x 79 in) Wheelbase: 2770 mm (109 in) Ground clearance: 300 mm (11.8 in) Minimum turning radius: 5600 mm (220.4 in) Fuel tank capacity: 40 L (10.57 gal) Curb weight: 773 kg (1704.1 lbs)

Payload capacity: 680 kg (1499.1 lbs) Towing capacity: 680 kg (1500 lbs)

Rear cargo box capacity: 300 kg (661.3 lbs)

Brakes

Four wheel hydraulic disc brake

Wheels

Front wheels:
Aluminum alloy (14 x 7 in)
Rear wheels:
Aluminum alloy (14 x 8 in)
Front tires: AT 27 x 9-14
Rear tires: AT 27 x 11-14

Transmission

CFMOTO clutch system: Variable transmission Gear box: P / R / N / H / L (parking lock shift system) Power train: 2WD / 4WD, locking front differential

Suspension and steering

Front suspension: Double A-arm independent, hydraulic shock absorber

Front travel: 225 mm (8.86 in)

Rear suspension: Double A-arm independent with sway bar, hydraulic shock absorber

Rear travel: 225 mm (8.86 in)

Steering: Electric Power Steering (EPS)

Liecific rower steering (EPS)

Protection plan

EASY protection plan available





5 Year limited warranty: 1 year complete with no mileage restriction + 48 months balance powertrain only or 5,000 km

Follow us



