# **ZFORCE 950** SPORT 2025



## The most equipped vehicles on the market More than \$5,600 in add-ons!

Maama Red

#### Standard features and benefits

**Twilight Blue** 

5-year CFMOTO warranty

Safety and convenience

Rims \$1,500 value


Nebula Black

**Trailer hitch** \$100 value

Roof \$500 value

3,500 lbs winch (complete assembly) \$1,000 value

Half doors \$1,500 value



\$1,000 value

## **Specifications**

#### Engine

Progressive nock spring

Type: V-Twin cylinder, liquid-cooled, SOHC, 8-valves, 4-strokes Displacement: 963 cc Bore & Stroke: 91 x 74 mm (3.5 x 2.91 in) Compression: 10.8:1 **Engine management:** Fuel injected engine Cooling system: Liquid Starting: Electric Battery: 30 Ah

### Size / weight

Length x Width x Height: 3065 x 1524 x 1870mm (120.6 x 60 x 73.6 in) Wheelbase: 2286 mm (90 in) Ground clearance: 305 mm (12 in) Minimum turning radius: 5250 mm (207 in) Fuel tank capacity: 37 L (9.77 gal) Curb weight: 689 kg (1519 lbs) Towing capacity: 680 kg (1500 lbs) Rear cargo box capacity:

150 kg (330.6 lbs)

#### **Brakes**

Four wheel brake disc

#### Special features

CFMOTO Ride app connectivity

#### Wheels

100 K

<u>Sport/N</u>ormal

Front wheels: Aluminum alloy  $(14 \times 7 \text{ in})$ **Rear wheels:** Aluminum alloy  $(14 \times 8 \text{ in})$ Front tires: 27 x 9 x 14 Rear tires: 27x 11 x 14

#### Transmission

CV-Tech IBC clutch system: Variable transmission Gear box: P/R/N/H/L (parking lock shift system) Power train: 2WD / 4WD. locking front differential

#### Suspension and steering

Front suspension: Double A-arm independent Front travel: 307 mm (12.1 in) **Rear suspension:** Double A link rod suspension Rear travel: 334 mm (13.1 in) Steering: Variable Electric Power Steering (EPS)

#### Protection plan

EASY protection plan available





restriction + 48 months balance powertrain only or 5,000 km

cfmoto.ca \*The pictures are for illustrative purposes only and accessories shown are not included. Specifications to change without notice. Details in store





