

2025 COMMANDER DPS



Compass Green / 700 / 1000R

ENGINES	700	1000R
Type	52 hp / 42 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc single cylinder, liquid-cooled	100 hp, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)	
Transmission	pDrive primary CVT with engine braking and electronic drive belt protection L / H / N / R / P	Quick Response System (QRS) CVT with high-airflow ventilation and electronic drive belt protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Visco-Lok [†] QE auto-locking front differential	Selectable Turf Mode / 2WD / 4WD auto-locking front differential
Driving Assistance	CVT Engine Braking SPORT / ECO™ modes	
Power Steering	Dynamic Power Steering (DPS™)	
SUSPENSIONS		
Front Suspension	Double A-arm with sway bar / 12.5 in. (31.8 cm) suspension travel	
Front Shocks	Twin-tube gas-charged shocks	
Rear Suspension	TTA with sway bar / 13 in. (33 cm) suspension travel	
Rear Shocks	Twin-tube gas-charged shocks	
TIRES & WHEELS		
Front / Rear Tires	XPS Trail Force 27 x 9/11 x 14 in.	
Wheels	14 in. steel	
BRAKES		
Front / Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers	

PACKAGE HIGHLIGHTS

700	1000R
<ul style="list-style-type: none"> • Visco-Lok[†] QE front differential • Rear differential with Turf mode • Dynamic Power Steering (DPS™) • SPORT / ECO™ modes • D.E.S.S. Key with Start / Stop button • 4.5 in. digital display • Premium half doors • Mudguards 	<ul style="list-style-type: none"> • Rear differential with Turf mode • Dynamic Power Steering (DPS™) • SPORT / ECO™ modes • D.E.S.S. Key with Start / Stop button • 4.5 in. digital display • Premium half doors • Mudguards

DIMENSIONS & CAPACITIES

	700	1000R
Estimated Dry Weight	1,530 lb (694 kg)	1,600 lb (725.5 kg)
Chassis / Cage	Profiled cage, ROPS-approved	
L x W x H	128.5 x 62 x 70.5 in. (326.4 x 157.5 x 180.2 cm)	
Wheelbase	90.6 in. (230.1 cm)	
Ground Clearance	12.5 in. (31.8 cm)	
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)	
Cargo Box Capacity	600 lb (272.2 kg)	
Towing Capacity	2,000 lb (907.2 kg)	
Payload Capacity	1,030 lb (467.2 kg)	
Storage Capacity	Total: 7.3 gal (27.6 L)	
Fuel Capacity	10 gal (38 L)	

FEATURES

Gauge	4.5 in. wide digital display
Instrumentation	DC outlet (10 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Magneto	650 W
Lighting	Front lighting output 110 W LED taillights
Winch	N/A
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors Full skid plate Mudguards
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP Limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months

can-am

© 2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. † Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SxS) operator's guide and watch the safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SxSs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold hand grips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly.

