

# *Big Jim*

## **SUPERFLEX-MAGNUM SERIES PACKER-PULVERISERS**



The Superflex concept has proven to be the most revolutionary design in packers for years, the independent floating design lets each section follow the contour of the soil giving more effective wheel to soil contact, the design also allows each section to independently float over obstacles such as stones without placing excessive weight on the gang causing wheel, shaft or bearing damage.

Construction of the "**Magnum Series**" allows us to produce 40 to 50 foot packers with 19" wheels and scrapers and have sufficient capacity to incorporate heavier large diameter wheels in the future should the demand arise.....



All plumbing neatly arranged and tied in place



Rugged 1 3/4" inch hinge pins, securely fastened



3 beam outerwing section w/two cylinders, each packer gang oscillates on centre pin and plastic wear plates.



Adjustable clevis hitch, safety chains, 7000 lb. tongue jack, steel hyd lines.



5 bearing main frame section, lights & reflectors standard.



Rugged 4 beam main wing section w/two cylinders.

## SPECIFICATIONS

- Transport Height..... 15ft (50' Model)
- Transport Width..... 16' 8" (All)
- Total Weight (46' w/19" wheels)..... 15058 lbs. (approx)
- Drawbar Weight (Transport position)..... 1100 lbs. (46' Model)
- Tongue Material..... 7" x 5" x 3/8 wall
- Tongue Brace Material..... 3" x 3" x 1/4 wall
- Main Frame Material..... 6" x 6" x 3/8" wall
- Inner Wing Front Tubes (2)..... 6" x 4" x 3/8" wall
- Inner Wing Rear Tubes (2)..... 6" x 4" x 1/4" wall
- Outer Wing Tubes..... 6" x 4" x 1/4" wall
- Wheel Gang Tubes..... 6" x 4" x 1/4 wall
- Pivot Pins and Gang Shafts..... 1 3/4" C.R. (C1045)
- Tires x 4..... 11L – 15 12 ply.
- Wheels x 4..... 6 bolt solid center
- Hubs x 4..... 6 bolt 5000 lb.
- Gang Shaft Bearings..... 1 3/4" NTN Triple Seal
- Hydraulic Cylinders..... 3000 PSI (CAN. Made)
- Hydraulic Connections..... JIC and ORB



## STANDARD FEATURES

- Forged Pintle/Clevis Adjustable Hitch
- 7000 lb Tongue Jack
- 3/8" Grd 70 20000 lb DOT for ag. Safety Chains x 2
- Tandem 4" x 24" Inner Wing Cylinders
- Tandem 3 1/2" x 24" Outer Wing Cylinders
- 2 Light-Steel Light Boxes
- 14/7 Heavy, Jacket , Wiring
- 7 Pin Aluminum Light Plug
- Reflective tape

## OPTIONS

- 18" Ductile Smooth Sprocket Combination Wheel
- 19" Ductile Notched (Rooster Comb) Wheel
- Scrapers for 19: Notched Wheels
- 20" Ductile Crowfoot Wheels

**Distributed in Canada by:**  
**HARCO AG EQUIPMENT**  
**HARRISTON, ON**  
**519-338-2923, www.harcoag.ca**  
**FAX: 519-338-2756**  
**Email: sales@harcoag.ca**

## DEALER CONTACT: